

# Package ‘OneSampleLogRankTest’

February 3, 2024

**Title** One-Sample Log-Rank Test

**Version** 0.9.2

**Imports** magrittr, dplyr, ggplot2, survival, survminer, rlang

**Description** The log-rank test is performed to assess the survival outcomes between two group. When there is no proper control group or obtaining such data is cumbersome, one sample log-rank test can be applied. This package performs one sample log-rank test as described in Finkelstein et al. (2003)<[doi:10.1093/jnci/djt227](https://doi.org/10.1093/jnci/djt227)> and variation of the test for small sample sizes which is detailed in FD Liddell (1984)<[doi:10.1136/jech.38.1.85](https://doi.org/10.1136/jech.38.1.85)> paper. Visualization function in the package generates Kaplan-Meier Curve comparing survival curve of the general population against that of the population of interest.

**License** GPL (>= 3)

**Encoding** UTF-8

**LazyData** true

**RoxygenNote** 7.1.2

**Suggests** knitr, rmarkdown

**VignetteBuilder** knitr

**NeedsCompilation** no

**Author** Divy Kangeyan [aut, cre],  
Jin Xie [aut]

**Maintainer** Divy Kangeyan <[dkangeyan@kitpharma.com](mailto:dkangeyan@kitpharma.com)>

**Depends** R (>= 3.5.0)

**Repository** CRAN

**Date/Publication** 2024-02-03 12:30:15 UTC

## R topics documented:

dataPop_1999_2020	2
dataPop_2018_2021	2
dataPop_2018_2021_race_sex_eth	3
dataSurv	4

dataSurv_small . . . . .	4
findMatchedCumSurvProb . . . . .	5
oneSampleLogRankTest . . . . .	6
plotKM . . . . .	6
simulated_clinical_data . . . . .	7

<b>Index</b>	<b>8</b>
--------------	----------

---

dataPop_1999_2020	<i>Population data (1999-2020)</i>
-------------------	------------------------------------

---

### Description

This data set contains mortality rate for various demographic groups by age. all column has overall mortality rate for all groups. Race groups are indicated by the following notation: w - white, b - black, ai - american indian and as - asian. Female and Males are indicated by an additional suffix `_f` and `_m`.

### Usage

```
dataPop_1999_2020
```

### Format

A dataframe with 16 columns and 151 rows.

### Source

CDC Wonder Database. Data Collected from 1999 - 2020

### References

<https://wonder.cdc.gov/>

---

dataPop_2018_2021	<i>Population data (2018_2021)</i>
-------------------	------------------------------------

---

### Description

This data set contains mortality rate for various demographic groups by age. all column has overall mortality rate for all groups. Race groups are indicated by the following notation: w - white, b - black, ai - american indian and as - asian, nh - native hawaiian. Female and Males are indicated by an additional suffix `_f` and `_m`.

### Usage

```
dataPop_2018_2021
```

**Format**

A dataframe with 19 columns and 151 rows.

**Source**

CDC Wonder Database. Data Collected from 2018\_2021

**References**

<https://wonder.cdc.gov/>

---

dataPop\_2018\_2021\_race\_sex\_eth

*Population data (2018\_2021) by race, sex, ethnicity*

---

**Description**

This data set contains mortality rate for various demographic groups by age. all column has overall mortality rate for all groups. Race groups are indicated by the following notation: w - white, b - black, ai - american indian and as - asian, nh - native hawaiian. Female and Males are indicated by an additional suffix \_f and \_m.

**Usage**

dataPop\_2018\_2021

**Format**

A dataframe with 16 columns and 151 rows.

**Source**

CDC Wonder Database. Data Collected from 2018\_2021

**References**

<https://wonder.cdc.gov/>

---

dataSurv

*Survival data*

---

**Description**

This data set is obtained from Finkelstein et al. paper that contains the following five columns: age, time, event status, sex and race.

**Usage**

dataSurv

**Format**

A dataframe with 5 columns and 33 rows.

**Source**

Finkelstein et al. (2003)

**References**

Finkelstein, D. M., Muzikansky, A., & Schoenfeld, D. A. (2003). Comparing survival of a sample to that of a standard population. *Journal of the National Cancer Institute*, 95(19), 1434-1439.

---

dataSurv\_small

*Survival data*

---

**Description**

This data set is subset of data obtained from Finkelstein et al. paper that contains the following five columns: age, time, event status, sex and race. In order to apply the exact test 12 patients were randomly selected out of 33 patients.

**Usage**

dataSurv

**Format**

A dataframe with 5 columns and 12 rows.

**Source**

Finkelstein et al. (2003)

## References

Finkelstein, D. M., Muzikansky, A., & Schoenfeld, D. A. (2003). Comparing survival of a sample to that of a standard population. *Journal of the National Cancer Institute*, 95(19), 1434-1439.

---

findMatchedCumSurvProb

*Find Matched Cumulative Survival Probability*

---

## Description

Find Matched Cumulative Survival Probability

## Usage

```
findMatchedCumSurvProb(time, ageDiag, sex, race, dataPop, maxFollowUp = NULL)
```

## Arguments

time	follow up length
ageDiag	age at diagnosis
sex	sex
race	race
dataPop	Population level mortality data
maxFollowUp	maximum follow-up, if max follow-up not provided then the time would be considered until death or censoring

## Value

matched survival probability

## Examples

```
# load data
data(dataSurv_small)
data(dataPop_2018_2021)

# Extract info for the first subject
time_vec <- dataSurv_small$time[1]
age_vec <- dataSurv_small$age[1]
sex_vec <- dataSurv_small$sex[1]
race_vec <- dataSurv_small$race[1]

# Generate cumulative survival probability
findMatchedCumSurvProb(time = time_vec, ageDiag = age_vec, sex = sex_vec,
  race = race_vec, dataPop = dataPop_2018_2021)

#If maximum followup is determined to be 20 years
```

```
findMatchedCumSurvProb(time = time_vec, ageDiag = age_vec, sex = sex_vec,
  race = race_vec, dataPop = dataPop_2018_2021, maxFollowUp = 20)
```

---

oneSampleLogRankTest *Calculate One-Sample Log-Rank Test*

---

### Description

Calculate One-Sample Log-Rank Test

### Usage

```
oneSampleLogRankTest(dataSurv, dataPop, type = c("exact", "approximate"))
```

### Arguments

dataSurv	Survival data
dataPop	Population data
type	Type of test

### Value

p-value for one-sample log-rank test

### Examples

```
# load data
data(dataSurv_small)
data(dataPop_2018_2021)

# Since the dataset is small run an exact test
oneSampleLogRankTest(dataSurv_small, dataPop_2018_2021, type = "exact")
```

---

plotKM *Plot Kaplan-Meier Curve against Population*

---

### Description

Plot Kaplan-Meier Curve against Population

### Usage

```
plotKM(dataSurv, dataPop, type = c("exact", "approximate"))
```

### Arguments

<code>dataSurv</code>	Survival data
<code>dataPop</code>	Population data
<code>type</code>	Type of test to conduct in order to display p-value

### Value

ggplot object

### Examples

```
# load data
data(dataSurv_small)
data(dataPop_2018_2021)

plotKM(dataSurv_small, dataPop_2018_2021, type = "exact")
```

---

`simulated_clinical_data`

*Simultaed Clinical data*

---

### Description

This data is simulated data from clinical trial data that contains five columns: race, sex, age, event status and time in years.

### Usage

```
simulated_clinical_data
```

### Format

A dataframe with 5 columns and 500 rows.

### Source

Simulated

### References

None

# Index

## \* datasets

- dataPop\_1999\_2020, [2](#)
- dataPop\_2018\_2021, [2](#)
- dataPop\_2018\_2021\_race\_sex\_eth, [3](#)
- dataSurv, [4](#)
- dataSurv\_small, [4](#)
- simulated\_clinical\_data, [7](#)

- dataPop\_1999\_2020, [2](#)
- dataPop\_2018\_2021, [2](#)
- dataPop\_2018\_2021\_race\_sex\_eth, [3](#)
- dataSurv, [4](#)
- dataSurv\_small, [4](#)

- findMatchedCumusurvProb, [5](#)

- oneSampleLogRankTest, [6](#)

- plotKM, [6](#)

- simulated\_clinical\_data, [7](#)