

Package ‘metavizr’

March 28, 2021

Type Package

Version 1.15.0

Maintainer Hector Corrada Bravo <hcorrada@gmail.com>

License MIT + file LICENSE

Title R Interface to the metaviz web app for interactive metagenomics data analysis and visualization

Description This package provides Websocket communication to the metaviz web app (<http://metaviz.cccb.umd.edu>) for interactive visualization of metagenomics data. Objects in R/bioc interactive sessions can be displayed in plots and data can be explored using a facetzoom visualization. Fundamental Bioconductor data structures are supported (e.g., MRExperiment objects), while providing an easy mechanism to support other data structures. Visualizations (using d3.js) can be easily added to the web app as well.

VignetteBuilder knitr

Depends R (>= 3.4), metagenomeSeq (>= 1.17.1), methods, data.table, Biobase, digest

Imports epivizr, epivizrData, epivizrServer, epivizrStandalone, vegan, GenomeInfoDb, phyloseq, httr

Suggests knitr, BiocStyle, matrixStats, msd16s (>= 0.109.1), etec16s, testthat, gss, curatedMetagenomicData

Collate 'metavizControl.R' 'startMetaviz.R' 'utils.R'
'EpivizMetagenomicsData-class.R' 'register-methods.R'
'validateMRExperiment.R' 'MetavizApp-class.R'
'MetavizGraph-class.R'
'EpivizMetagenomicsDataInnerNodes-class.R'
'MetavizGraphInnerNodes-class.R'
'EpivizMetagenomicsDataTimeSeries-class.R'

biocViews Visualization, Infrastructure, GUI, Metagenomics, ImmunoOncology

RoxygenNote 6.1.1

git_url <https://git.bioconductor.org/packages/metavizr>

git_branch master

git_last_commit 24e40f9

git_last_commit_date 2020-10-27

Date/Publication 2021-03-28

Author Hector Corrada Bravo [cre, aut],

Florin Chelaru [aut],

Justin Wagner [aut],

Jayaram Kancherla [aut],

Joseph Paulson [aut]

R topics documented:

buildMetavizGraph	2
buildMetavizGraphInnerNodes	3
EpivizMetagenomicsData-class	4
EpivizMetagenomicsDataInnerNodes-class	6
EpivizMetagenomicsDataTimeSeries-class	8
generateSelection	8
MetavizApp-class	9
metavizControl	9
MetavizGraph-class	10
MetavizGraphInnerNodes-class	10
register,MRExperiment-method	10
register,phyloseq-method	11
replaceNAFeatures	11
setMetavizStandalone	12
startMetaviz	13
startMetavizStandalone	13
validateObject	14
Index	15

buildMetavizGraph	<i>Build a MetavizTree object from another object</i>
-------------------	---

Description

Build a MetavizTree object from another object

Usage

```
buildMetavizGraph(object, ...)
```

```
## S4 method for signature 'MRExperiment'
```

```
buildMetavizGraph(object, feature_order, ...)
```

Arguments

object	The object from which taxonomy data is extracted
...	Additional arguments
feature_order	Ordering of leaves (features) in taxonomy tree

Value

a [MetavizGraph](#) object

Methods (by class)

- MRExperiment: Build graph from a [MRExperiment-class](#) object

buildMetavizGraphInnerNodes

Build a MetavizTree object from another object

Description

Build a MetavizTree object from another object

Usage

```
buildMetavizGraphInnerNodes(object, ...)
```

```
## S4 method for signature 'MRExperiment'
buildMetavizGraphInnerNodes(object, feature_order,
...)
```

Arguments

object	The object from which taxonomy data is extracted
...	Additional arguments
feature_order	Ordering of leaves (features) in taxonomy tree

Value

a [MetavizGraphInnerNodes](#) object

Methods (by class)

- MRExperiment: Build graph from a [MRExperiment-class](#) object

EpivizMetagenomicsData-class

Data container for MRExperiment objects

Description

Used to serve metagenomic data (used in e.g., icle plots and heatmaps). Wraps [MRExperiment-class](#) objects.

Methods

`df_to_tree(root, df)` Helper function to recursively build nested response for `getHierarchy`

root Root of subtree

df data.frame containing children to process

`get_default_chart_type()` Get name of default chart type for this data type

`get_measurements()` Get description of measurements served by this object

`getAlphaDiversity(measurements = NULL)` Compute alpha diversity using vegan for the given samples

measurements Samples to compute alpha diversity

start Start of feature range to query

end End of feature range to query

`getCombined(measurements = NULL, seqName, start = 1, end = 1000, order = NULL, nodeSelection = NULL, select)`
Return the counts aggregated to selected nodes for the given samples

measurements Samples to get counts for

seqName name of datasource

start Start of feature range to query

end End of feature range to query

order Ordering of nodes

nodeSelection Node-id and selectionType pairs

selectedLevels Current aggregation level

`getHierarchy(nodeId = NULL)` Retrieve feature hierarchy information for subtree with specified root

nodeId Feature identifier with level info

`getPCA(measurements = NULL)` Compute PCA over all features for given samples

measurements Samples to compute PCA over

start Start of feature range to query

end End of feature range to query

`getRows(measurements = NULL, start = 1, end = 1000, selectedLevels = 3, selections = NULL)`
Return the sample annotation and features within the specified range and level for a given sample and features

measurements Samples to retrieve for
start Start of feature range to query
end End of feature range to query
selections Node-id and selectionType pairs
selectedLevels Current aggregation level
getValues(measurements = NULL, start = 1, end = 1000, selectedLevels = 3, selections = NULL, row_order = NULL)
Return the counts for a sample within the specified range
measurements Samples to get counts for
start Start of feature range to query
end End of feature range to query
selections Node-id and selectionType pairs
selectedLevels Current aggregation level
propagateHierarchyChanges(selection = NULL, order = NULL, selectedLevels = NULL, request_with_labels = FALSE)
Update internal state for hierarchy
selection Node-id and selectionType pairs
order Ordering of features
selectedLevels Current aggregation level
request_with_labels For handling requests using fData entries from MRExperiment
row_to_dict(row) Helper function to format each node entry for getHierarchy response
row Information for current node.
searchTaxonomy(query = NULL, max_results = 15) Return list of features matching a text-based query
query String of feature for which to search
max_results Maximum results to return
toNEO4JDbHTTP(batch_url, neo4juser, neo4jpass, datasource, description = NULL) Write an 'EpivizMetagenomicsData' object to a Neo4j graph database
@param batch_url (character) Neo4j database url and port for processing batch http requests
@param neo4juser (character) Neo4j database user name @param neo4jpass (character) Neo4j database password @param datasource (character) Name of Neo4j datasource node for this 'EpivizMetagenomicsData' object
@examples library(metagenomeSeq) data("mouseData") mobj <- metavizr:::EpivizMetagenomicsData\$new(object=mouseData)
mobj\$toNEO4JDbHTTP(batch_url = "http://localhost:7474/db/data/batch", neo4juser = "neo4juser", neo4jpass = "neo4jpass", datasource = "mouse_data")
update(new_object, send_request = TRUE) Update underlying data object with new object

Examples

```

## Not run:
library(metagenomeSeq)
data(mouseData)
obj <- metavizr:::EpivizMetagenomicsData$new(mouseData, feature_order = colnames(fData(mouseData)))

## End(Not run)

```

 EpivizMetagenomicsDataInnerNodes-class

Data container for MRExperiment objects

Description

Used to serve metagenomic data (used in e.g., icle plots and heatmaps). Wraps [MRExperiment-class](#) objects.

Methods

`df_to_tree(root, df)` Helper function to recursively build nested response for `getHierarchy`

root Root of subtree

df data.frame containing children to process

`get_default_chart_type()` Get name of default chart type for this data type

`get_measurements()` Get description of measurements served by this object

`getAlphaDiversity(measurements = NULL)` Compute alpha diversity using vegan for the given samples

measurements Samples to compute alpha diversity

start Start of feature range to query

end End of feature range to query

`getCombined(measurements = NULL, seqName, start = 1, end = 1000, order = NULL, nodeSelection = NULL, select)`
Return the counts aggregated to selected nodes for the given samples

measurements Samples to get counts for

seqName name of datasource

start Start of feature range to query

end End of feature range to query

order Ordering of nodes

nodeSelection Node-id and selectionType pairs

selectedLevels Current aggregation level

`getHierarchy(nodeId = NULL)` Retrieve feature hierarchy information for subtree with specified root

nodeId Feature identifier with level info

`getPCA(measurements = NULL)` Compute PCA over all features for given samples

measurements Samples to compute PCA over

start Start of feature range to query

end End of feature range to query

`getRows(measurements = NULL, start = 1, end = 1000, selectedLevels = 3, selections = NULL)`
Return the sample annotation and features within the specified range and level for a given sample and features

measurements Samples to retrieve for
start Start of feature range to query
end End of feature range to query
selections Node-id and selectionType pairs
selectedLevels Current aggregation level

getValues(measurements = NULL, start = 1, end = 1000, selectedLevels = 3, selections = NULL)
 Return the counts for a sample within the specified range

measurements Samples to get counts for
start Start of feature range to query
end End of feature range to query
selections Node-id and selectionType pairs
selectedLevels Current aggregation level

propagateHierarchyChanges(selection = NULL, order = NULL, selectedLevels = NULL, request_with_labels = FALSE)
 Update internal state for hierarchy

selection Node-id and selectionType pairs
order Ordering of features
selectedLevels Current aggregation level
request_with_labels For handling requests using fData entries from MRexperiment

row_to_dict(row) Helper function to format each node entry for getHierarchy response

row Information for current node.

searchTaxonomy(query = NULL, max_results = 15) Return list of features matching a text-based query

query String of feature for which to search
max_results Maximum results to return

Examples

```
## Not run:
library(curatedMetagenomicData)
zeller.eset = ZellerG_2014.metaphlan_bugs_list.stool()
zeller_MR <- ExpressionSet2MRexperiment(zeller.eset)
feature_order <- colnames(fData(zeller_MR))
sampleId<- "CCIS98482370ST-3-0"
mObj <- metavizr::EpivizMetagenomicsDataInnerNodes$new(zeller_MR, feature_order = feature_order)

## End(Not run)
```

EpivizMetagenomicsDataTimeSeries-class
Data container for MExperiment objects

Description

Used to serve metagenomic data (used in e.g., icle plots and heatmaps). Wraps [MExperiment-class](#) objects.

Examples

```
## Not run:
library(metagenomeSeq)
data(mouseData)
obj <- metavizr:::EpivizMetagenomicsData$new(mouseData, feature_order = colnames(fData(mouseData)))

## End(Not run)
```

generateSelection *Method to select and set aggregation type to nodes in FacetZoom*

Description

Method to select and set aggregation type to nodes in FacetZoom

Usage

```
generateSelection(feature_names, aggregation_level, selection_type,
  feature_order = NULL)
```

Arguments

```
feature_names   Selected Features
aggregation_level
                 Level in the hierarchy
selection_type   Expanded, aggregated, or removed
feature_order   Order of features at that level
```

Value

A selection object for a metavizControl object to accept

Examples

```
generateSelection("Bacteroidales", 1L, 2L)
```

MetavizApp-class	<i>Class managing connection to metaviz application.</i>
------------------	--

Description

Class managing connection to metaviz application.

metavizControl	<i>metavizr settings</i>
----------------	--------------------------

Description

Default settings for the various plotting functions in metavizr.

Usage

```
metavizControl(aggregateAtDepth = 3, aggregateFun = function(x)
  colSums(x), valuesAnnotationFuns = NULL, maxDepth = 4,
  maxHistory = 3, maxValue = NULL, minValue = NULL, title = "",
  n = 10000, rankFun = stats::sd, norm = TRUE, log = FALSE,
  featureSelection = NULL)
```

Arguments

aggregateAtDepth	Level of the tree to aggregate counts at by default.
aggregateFun	Function to aggregate counts by at the aggregateAtDepth level.
valuesAnnotationFuns	Function for error bars.
maxDepth	Level of the tree to display by default in icicle view.
maxHistory	Value for caching.
maxValue	Maximum value to display.
minValue	Minimum value to display.
title	title.
n	Number of OTUs to include in ranking.
rankFun	Ranking function - single vector function.
norm	Normalize MRexperiment object.
log	Log tranformation of MRexperiment object.
featureSelection	List of features to set as nodeSelections

Value

List of setting parameters.

Examples

```
settings = metavizControl()
```

MetavizGraph-class	<i>Graph implementation to query hierarchical feature data</i>
--------------------	--

Description

Used to manage aggregation and range queries from the Metaviz app UI.

MetavizGraphInnerNodes-class	<i>Graph implementation to query hierarchical feature data</i>
------------------------------	--

Description

Used to manage aggregation and range queries from the Metaviz app UI.

register,MRexperiment-method	<i>Generic method to register data to the epiviz data server</i>
------------------------------	--

Description

Generic method to register data to the epiviz data server

Usage

```
## S4 method for signature 'MRexperiment'
register(object, type = "LeafCounts",
        columns = NULL, ...)
```

Arguments

object	The object to register to data server
type	leafCounts, if data objects has counts at leaf level or innerNodeCounts, if data object has counts at inner nodes
columns	Name of columns containing data to register
...	Additional arguments passed to object constructors

Value

An [EpivizMetagenomicsData-class](#) object

register,phyloseq-method

Generic method to register data to the epiviz data server

Description

Generic method to register data to the epiviz data server

Usage

```
## S4 method for signature 'phyloseq'
register(object, type = "LeafCounts", ...)
```

Arguments

object	The object to register to data server
type	leafCounts, if data objects has counts at leaf level or innerNodeCounts, if data object has counts at inner nodes
...	Additional arguments passed to object constructors

Value

An [phyloseq-class](#) object

replaceNAFeatures	<i>Method to replace NA or null feature labels with Not_Annotated_hierarchy-level</i>
-------------------	---

Description

Method to replace NA or null feature labels with Not_Annotated_hierarchy-level

Usage

```
replaceNAFeatures(replacing_na_obj_fData, feature_order)
```

Arguments

replacing_na_obj_fData	fData from MRexperiment object to replace NA or null
feature_order	Order of features

Value

hierarchy with NA or null feature labels replaced

Examples

```
library(metagenomeSeq)
data(mouseData)
feature_order <- colnames(fData(mouseData))
replaceNAFeatures(fData(mouseData), feature_order)
```

setMetavizStandalone *set metaviz app standalone settings*

Description

set metaviz app standalone settings

Usage

```
setMetavizStandalone(url = "https://github.com/epiviz/epiviz.git",
  branch = "metaviz-4.1", local_path = NULL, non_interactive = FALSE)
```

Arguments

url	(character) github url to use. defaults to ("https://github.com/epiviz/epiviz.git").
branch	(character) branch on the github repository. defaults to (master).
local_path	(character) if you already have a local instance of metaviz and would like to run standalone use this.
non_interactive	(logical) don't download repo, used for testing purposes.

Value

path to the metaviz app git repository

Examples

```
## Not run:
#' # see package vignette for example usage
setMetavizStandalone()

## End(Not run)
```

startMetaviz	<i>Start metaviz app and create MetavizApp object to manage connection.</i>
--------------	---

Description

Start metaviz app and create [MetavizApp](#) object to manage connection.

Usage

```
startMetaviz(host = "http://metaviz.cbcb.umd.edu",  
  register_function = .register_all_metaviz_things, ...)
```

Arguments

host	(character) host address to launch.
register_function	(function) function used to register actions and charts on the metaviz app.
...	additional parameters passed to startEpiviz .

Value

An object of class [MetavizApp](#)

See Also

[MetavizApp](#)

Examples

```
# see package vignette for example usage  
app <- startMetaviz(non_interactive=TRUE, open_browser=FALSE)  
app$stop_app()
```

startMetavizStandalone	<i>Start metaviz app in standalone (locally) and create MetavizApp object to manage connection.</i>
------------------------	---

Description

Start metaviz app in standalone (locally) and create [MetavizApp](#) object to manage connection.

Usage

```
startMetavizStandalone(register_function = .register_all_metaviz_things,
  use_viewer_option = FALSE, ...)
```

Arguments

```
register_function
  (function) function used to register actions and charts on the metaviz app.
use_viewer_option
  (function) run application in viewer defined by getOption("viewer"). This
  allows standalone app to run in Rstudio's viewer (FALSE by default)
...
  additional parameters passed to startStandalone.
```

Value

An object of class [MetavizApp](#)

Examples

```
## see package vignette for example usage
app <- startMetavizStandalone(non_interactive=TRUE)
app$stop_app()
```

validateObject	<i>validate</i> MExperiment-class object
----------------	--

Description

validate [MExperiment-class](#) object

Usage

```
validateObject(object)
```

Arguments

```
object          an object of class MExperiment-class
```

Value

TRUE or FALSE

Examples

```
library(metagenomeSeq)
data(mouseData)
validateObject(mouseData)
```

Index

buildMetavizGraph, [2](#)
buildMetavizGraph, MRexperiment-method
 (buildMetavizGraph), [2](#)
buildMetavizGraphInnerNodes, [3](#)
buildMetavizGraphInnerNodes, MRexperiment-method
 (buildMetavizGraphInnerNodes),
 [3](#)

EpivizMetagenomicsData
 (EpivizMetagenomicsData-class),
 [4](#)
EpivizMetagenomicsData-class, [4](#)
EpivizMetagenomicsDataInnerNodes
 (EpivizMetagenomicsDataInnerNodes-class),
 [6](#)
EpivizMetagenomicsDataInnerNodes-class,
 [6](#)
EpivizMetagenomicsDataTimeSeries
 (EpivizMetagenomicsDataTimeSeries-class),
 [8](#)
EpivizMetagenomicsDataTimeSeries-class,
 [8](#)

generateSelection, [8](#)

MetavizApp, [13](#), [14](#)
MetavizApp (MetavizApp-class), [9](#)
MetavizApp-class, [9](#)
metavizControl, [9](#)
MetavizGraph, [3](#)
MetavizGraph (MetavizGraph-class), [10](#)
MetavizGraph-class, [10](#)
MetavizGraphInnerNodes, [3](#)
MetavizGraphInnerNodes
 (MetavizGraphInnerNodes-class),
 [10](#)
MetavizGraphInnerNodes-class, [10](#)
MRexperiment-class, [14](#)

register, MRexperiment-method, [10](#)
register, phyloseq-method, [11](#)
replaceNAFeatures, [11](#)

setMetavizStandalone, [12](#)
startEpiviz, [13](#)
startMetaviz, [13](#)
startMetavizStandalone, [13](#)
startStandalone, [14](#)

validateObject, [14](#)