

# Package ‘bsseq’

April 12, 2022

**Version** 1.30.0

**Encoding** UTF-8

**Title** Analyze, manage and store bisulfite sequencing data

**Description** A collection of tools for analyzing and visualizing bisulfite sequencing data.

**Depends** R (>= 4.0), methods, BiocGenerics, GenomicRanges (>= 1.41.5), SummarizedExperiment (>= 1.19.5)

**Imports** IRanges (>= 2.23.9), GenomeInfoDb, scales, stats, graphics, Biobase, locfit, gtools, data.table (>= 1.11.8), S4Vectors (>= 0.27.12), R.utils (>= 2.0.0), DelayedMatrixStats (>= 1.5.2), permute, limma, DelayedArray (>= 0.15.16), Rcpp, BiocParallel, BSgenome, Biostrings, utils, HDF5Array (>= 1.19.11), rhdf5

**Suggests** testthat, bsseqData, BiocStyle, rmarkdown, knitr, Matrix, doParallel, rtracklayer, BSgenome.Hsapiens.UCSC.hg38, beachmat (>= 1.5.2), BatchJobs

**Collate** utils.R hasGRanges.R BSseq-class.R BSseqTstat\_class.R BSseq\_utils.R combine.R read.bsmooth.R read.bismark.R BSmooth.R BSmooth.tstat.R dmrFinder.R gof\_stats.R plotting.R fisher.R permutations.R BSmooth.fstat.R BSseqStat\_class.R getStats.R hdf5\_utils.R DelayedArray\_utils.R collapseBSseq.R FWIRanges-class.R FWGRanges-class.R findLoci.R

**License** Artistic-2.0

**VignetteBuilder** knitr

**URL** <https://github.com/kasperdanielhansen/bsseq>

**BugReports** <https://github.com/kasperdanielhansen/bsseq/issues>

**biocViews** DNAMethylation

**SystemRequirements** C++11

**LinkingTo** Rcpp, beachmat

**NeedsCompilation** yes

**RoxygenNote** 7.1.0

**git\_url** <https://git.bioconductor.org/packages/bsseq>  
**git\_branch** RELEASE\_3\_14  
**git\_last\_commit** 7eb5223  
**git\_last\_commit\_date** 2021-10-26  
**Date/Publication** 2022-04-12  
**Author** Kasper Daniel Hansen [aut, cre],  
 Peter Hickey [aut]  
**Maintainer** Kasper Daniel Hansen <kasperdanielhansen@gmail.com>

## R topics documented:

BS.chr22	2
BSsmooth	3
BSsmooth.tstat	7
BSseq	9
BSseq-class	10
BSseqStat-class	13
BSseqTstat-class	15
data.frame2GRanges	16
dmrFinder	17
findLoci	19
fisherTests	20
FWGRanges-class	22
getCoverage	22
getMeth	24
getStats	25
GoodnessOfFit	26
hasGRanges-class	28
plotRegion	29
read.bismark	31
read.bsmooth	37
read.umtab	38
<b>Index</b>	<b>40</b>

---

BS.chr22	<i>Whole-genome bisulfite sequencing for chromosome 22 from Lister et al.</i>
----------	---

---

## Description

This dataset represents chromosome 22 from the IMR90 cell line sequenced in Lister et al. Only CpG methylation are included (there were very few non-CpG loci). The two samples are two different extractions from the same cell line (ie. technical replicates), and are pooled in the analysis in the original paper.

**Usage**

```
data(BS.chr22)
```

**Format**

An object of class BSseq.

**Details**

All coordinates are in hg18.

**Source**

Obtained from [http://neomorph.salk.edu/human\\_methylome/data.html](http://neomorph.salk.edu/human_methylome/data.html) specifically the files [mc\\_imr90\\_r1.tar.gz](#) and [mc\\_imr90\\_r2.tar.gz](#). A script which downloads these files and constructs the BS.chr22 object may be found in 'inst/scripts/get\_BS.chr22.R', see the example.

**References**

R Lister et al. *Human DNA methylomes at base resolution show widespread epigenomic differences*. Nature (2009) 462, 315-322.

**Examples**

```
data(BS.chr22)
BS.chr22

script <- system.file("scripts", "get_BS.chr22.R", package = "bsseq")
script
readLines(script)
```

---

BSmooth

*BSmooth, smoothing bisulfite sequence data*

---

**Description**

This implements the BSmooth algorithm for estimating methylation levels from bisulfite sequencing data.

**Usage**

```
BSmooth(BSseq,
        ns = 70,
        h = 1000,
        maxGap = 10^8,
        keep.se = FALSE,
        BPPARAM = bpparam(),
        chunkdim = NULL,
        level = NULL,
        verbose = getOption("verbose"))
```

## Arguments

BSseq	An object of class BSseq.
ns	The minimum number of methylation loci in a smoothing window.
h	The minimum smoothing window, in bases.
maxGap	The maximum gap between two methylation loci, before the smoothing is broken across the gap. The default smoothes each chromosome separately.
keep.se	Should the estimated standard errors from the smoothing algorithm be kept. This will make the return object roughly 30 percent bigger and is currently not be used for anything in <b>bsseq</b> .
BPPARAM	An optional <a href="#">BiocParallelParam</a> instance determining the parallel back-end to be used during evaluation. Currently supported are <a href="#">SerialParam</a> (Unix, Mac, Windows), <a href="#">MulticoreParam</a> (Unix and Mac), <a href="#">SnowParam</a> (Unix, Mac, and Windows, limited to single-machine clusters), and <a href="#">BatchJobsParam</a> (Unix, Mac, Windows, only with the in-memory realization backend). See sections 'Parallelization and progress monitoring' and 'Realization backends' for further details.
chunkdim	<b>Only applicable if</b> <code>BACKEND == "HDF5Array"</code> . The dimensions of the chunks to use for writing the data to disk. By default, <code>getHDF5DumpChunkDim()</code> using the dimensions of the returned <a href="#">BSseq</a> object will be used. See <code>?{getHDF5DumpChunkDim}</code> for more information.
level	<b>Only applicable if</b> <code>BACKEND == "HDF5Array"</code> . The compression level to use for writing the data to disk. By default, <code>getHDF5DumpCompressionLevel()</code> will be used. See <code>?getHDF5DumpCompressionLevel</code> for more information.
verbose	A logical(1) indicating whether progress messages should be printed (default TRUE).

## Details

ns and h are passed to the `locfit` function. The bandwidth used is the maximum (in genomic distance) of the h and a width big enough to contain ns number of methylation loci.

## Value

An object of class BSseq, containing coefficients used to fit smoothed methylation values and optionally standard errors for these.

## Realization backends

The `BSmooth()` function creates a new assay to store the coefficients used to construct the smoothed methylation estimates (`coef`). An additional assay is also created if `keep.se == TRUE` (`se.coef`).

The choice of *realization backend* controls whether these assay(s) are stored in-memory as an ordinary [matrix](#) or on-disk as a [HDF5Array](#), for example.

The choice of realization backend is controlled by the `BACKEND` argument, which defaults to the current value of `DelayedArray::getAutoRealizationBackend()`.

BSmooth supports the following realization backends:

- NULL (in-memory): This stores each new assay in-memory using an ordinary [matrix](#).
- HDF5Array (on-disk): This stores each new assay on-disk in a HDF5 file using an [HDF5Matrix](#) from [HDF5Array](#).

Please note that certain combinations of realization backend and parallelization backend are currently not supported. For example, the [HDF5Array](#) realization backend is currently only compatible when used with a single-machine parallelization backend (i.e. it is not compatible with a [SnowParam](#) that specifies an *ad hoc* cluster of **multiple** machines). `BSmooth()` will issue an error when given such incompatible realization and parallelization backends. Furthermore, to avoid memory usage blow-ups, `BSmooth()` will issue an error if an in-memory realization backend is used when smoothing a disk-backed [BSseq](#) object.

Additional arguments related to the realization backend can be passed via the `...` argument. These arguments must be named and are passed to the relevant [RealizationSink](#) constructor. For example, the `...` argument can be used to specify the path to the HDF5 file to be used by `BSmooth()`. Please see the examples at the bottom of the page.

### Parallelization and progress monitoring

`BSmooth()` now uses the [BiocParallel](#) package to implement parallelization. This brings some notable improvements:

- Smoothed results can now be written directly to an on-disk realization backend by the worker. This dramatically reduces memory usage compared to previous versions of [bsseq](#) that required all results be retained in-memory.
- Parallelization is now supported on Windows through the use of a [SnowParam](#) object as the value of `BPPARAM`.
- Detailed and extensive job logging facilities.

All parallelization options are controlled via the `BPPARAM` argument. In general, we recommend that users combine multicore (single-machine) parallelization with an on-disk realization backend (see section, 'Realization backend'). For Unix and Mac users, this means using a [MulticoreParam](#). For Windows users, this means using a single-machine [SnowParam](#). Please consult the [BiocParallel](#) documentation to take full advantage of the more advanced features.

**Deprecated arguments:** `parallelBy`, `mc.cores`, and `mc.preschedule` are deprecated and will be removed in subsequent releases of [bsseq](#). These arguments were necessary when `BSmooth()` used the [parallel](#) package to implement parallelization, but this functionality is superseded by the aforementioned use of [BiocParallel](#). We recommend that users who previously relied on these arguments switch to `BPPARAM = MulticoreParam(workers = mc.cores, progressbar = TRUE)`.

**Progress monitoring:** A useful feature of [BiocParallel](#) are progress bars to monitor the status of long-running jobs, such as `BSmooth()`. Progress bars are controlled via the `progressbar` argument in the [BiocParallelParam](#) constructor. Progress bars replace the use of the deprecated verbose argument to print out information on the status of `BSmooth()`.

[BiocParallel](#) also supports extensive and detailed logging facilities. Please consult the [BiocParallel](#) documentation to take full advantage these advanced features.

**Author(s)**

Method and original implementation by Kasper Daniel Hansen <khansen@jhsph.edu>. Updated implementation to support disk-backed [BSseq](#) objects and more general parallelization by Peter Francis Hickey.

**References**

KD Hansen, B Langmead, and RA Irizarry. *BSmooth: from whole genome bisulfite sequencing reads to differentially methylated regions*. *Genome Biology* (2012) 13:R83. doi:[10.1186/gb-2012-13-10-r83](https://doi.org/10.1186/gb-2012-13-10-r83).

**See Also**

[locfit](#) in the [locfit](#) package, as well as [BSseq](#).

**Examples**

```
## Not run:
# Run BSmooth() on a matrix-backed BSseq object using an in-memory realization
# backend with serial evaluation.
data(BS.chr22)
# This is a matrix-backed BSseq object.
sapply(assays(BS.chr22, withDimnames = FALSE), class)
BS.fit <- BSmooth(BS.chr22, BPPARAM = SerialParam(progressbar = TRUE))
# The new 'coef' assay is an ordinary matrix.
sapply(assays(BS.fit, withDimnames = FALSE), class)
BS.fit

# Run BSmooth() on a disk-backed BSseq object using the HDF5Array realization
# backend (with data written to the file 'BSmooth_example.h5') with
# multi-core parallel evaluation.
BS.chr22 <- realize(BS.chr22, "HDF5Array")
# This is a disk-backed BSseq object.
sapply(assays(BS.chr22, withDimnames = FALSE), class)
BS.fit <- BSmooth(BS.chr22,
                  BPPARAM = MulticoreParam(workers = 2, progressbar = TRUE),
                  BACKEND = "HDF5Array",
                  filepath = "BSmooth_example.h5")
# The new 'coef' assay is an HDF5Matrix.
sapply(assays(BS.fit, withDimnames = FALSE), class)
BS.fit
# The new 'coef' assay is in the HDF5 file 'BSmooth_example.h5' (in the
# current working directory).
sapply(assays(BS.fit, withDimnames = FALSE), path)

## End(Not run)
```

---

BSmooth.tstat	<i>Compute t-statistics based on smoothed whole-genome bisulfite sequencing data.</i>
---------------	---

---

## Description

Compute t-statistics based on smoothed whole-genome bisulfite sequencing data.

## Usage

```
BSmooth.tstat(BSseq, group1, group2,
  estimate.var = c("same", "paired", "group2"), local.correct = TRUE,
  maxGap = NULL, qSd = 0.75, k = 101, mc.cores = 1, verbose = TRUE)
```

## Arguments

BSseq	An object of class BSseq.
group1	A vector of sample names or indexes for the ‘treatment’ group.
group2	A vector of sample names or indexes for the ‘control’ group.
estimate.var	How is the variance estimated, see details.
local.correct	A logical; should local correction be used, see details.
maxGap	A scalar greater than 0, see details.
qSd	A scalar between 0 and 1, see details.
k	A positive scalar, see details.
mc.cores	The number of cores used. Note that setting mc.cores to a value greater than 1 is not supported on MS Windows, see the help page for mclapply.
verbose	Should the function be verbose?

## Details

T-statistics are formed as the difference in means between group 1 and group 2 divided by an estimate of the standard deviation, assuming that the variance in the two groups are the same (same), that we have paired samples (paired) or only estimate the variance based on group 2 (group2). The standard deviation estimates are then smoothed (using a running mean with a width of k) and thresholded (using qSd which sets the minimum standard deviation to be the qSd-quantile). Optionally, the t-statistics are corrected for low-frequency patterns.

It is sometimes useful to use local.correct even if no large scale changes in methylation have been found; it makes the marginal distribution of the t-statistics more symmetric.

Additional details in the reference.

## Value

An object of class BSseqTstat.

**Author(s)**

Kasper Daniel Hansen <khansen@jhsp.h.edu>

**References**

KD Hansen, B Langmead, and RA Irizarry. *BSmooth: from whole genome bisulfite sequencing reads to differentially methylated regions*. Genome Biology (2012) 13:R83. doi:[10.1186/gb-2012-13-10-r83](https://doi.org/10.1186/gb-2012-13-10-r83).

**See Also**

[BSmooth](#) for the input object and [BSseq](#) for its class. [BSseqTstat](#) describes the return class. This function is likely to be followed by the use of [dmrFinder](#). And finally, see the package vignette(s) for more information on how to use it.

**Examples**

```
if(require(bsseqData)) {
  data(keepLoci.ex)
  data(BS.cancer.ex.fit)
  BS.cancer.ex.fit <- updateObject(BS.cancer.ex.fit)
  ## Remember to subset the BSseq object, see vignette for explanation
  BS.tstat <- BSmooth.tstat(BS.cancer.ex.fit[keepLoci.ex,],
    group1 = c("C1", "C2", "C3"),
    group2 = c("N1", "N2", "N3"),
    estimate.var = "group2")

  BS.tstat
  ## This object is also stored as BS.cancer.ex.tstat in the
  ## bsseqData package

  #-----
  # An example using a HDF5Array-backed BSseq object
  #

  library(HDF5Array)
  # See ?SummarizedExperiment::saveHDF5SummarizedExperiment for details
  hdf5_BS.cancer.ex.fit <- saveHDF5SummarizedExperiment(
    x = BS.cancer.ex.fit[keepLoci.ex, ],
    dir = tempfile())
  hdf5_BS.tstat <- BSmooth.tstat(hdf5_BS.cancer.ex.fit,
    group1 = c("C1", "C2", "C3"),
    group2 = c("N1", "N2", "N3"),
    estimate.var = "group2")
}
```



BSseq

*The constructor function for BSseq objects.***Description**

The constructor function for BSseq objects.

**Usage**

```
BSseq(M = NULL, Cov = NULL, coef = NULL, se.coef = NULL,
      trans = NULL, parameters = NULL, pData = NULL, gr = NULL,
      pos = NULL, chr = NULL, sampleNames = NULL, rmZeroCov = FALSE)
```

**Arguments**

M	A matrix-like object of methylation evidence (see 'Details' below).
Cov	A matrix-like object of coverage (see 'Details' below).
coef	A matrix-like object of smoothing estimates (see 'Details' below).
se.coef	A matrix-like object of smoothing standard errors (see 'Details' below).
trans	A smoothing transformation.
parameters	A list of smoothing parameters.
pData	An data.frame or <a href="#">DataFrame</a> .
sampleNames	A vector of sample names.
gr	An object of type <a href="#">GRanges</a> .
pos	A vector of locations.
chr	A vector of chromosomes.
rmZeroCov	Should genomic locations with zero coverage in all samples be removed.

**Details**

The 'M', 'Cov', 'coef', and 'se.coef' matrix-like objects will be coerced to [DelayedMatrix](#) objects; see `?DelayedArray::DelayedMatrix` for the full list of supported matrix-like objects. We recommend using [matrix](#) objects for in-memory storage of data and [HDF5Matrix](#) for on-disk storage of data.

Genomic locations are specified either through `gr` or through `chr` and `pos` but not both. There should be the same number of genomic locations as there are rows in the M and Cov matrix.

The argument `rmZeroCov` may be useful in order to reduce the size of the return object by removing methylation loci with zero coverage.

In case one or more methylation loci appears multiple times, the M and Cov matrices are summed over rows linked to the same methylation loci. See the example below.

Users should never have to specify `coef`, `se.coef`, `trans`, and `parameters`, this is for internal use (they are added by `BSmooth`).

`phenoData` is a way to specify pheno data (as known from the `ExpressionSet` and `eSet` classes), at a minimum `sampleNames` should be given (if they are not present, the function uses `col.names(M)`).

**Value**

An object of class BSseq.

**Author(s)**

Kasper Daniel Hansen <khansen@jhsph.edu>

**See Also**

[BSseq](#)

**Examples**

```
M <- matrix(0:8, 3, 3)
Cov <- matrix(1:9, 3, 3)
BS1 <- BSseq(chr = c("chr1", "chr2", "chr1"), pos = c(1,2,3),
             M = M, Cov = Cov, sampleNames = c("A", "B", "C"))
BS1
BS2 <- BSseq(chr = c("chr1", "chr1", "chr1"), pos = c(1,1,1),
             M = M, Cov = Cov, sampleNames = c("A", "B", "C"))
BS2
```

```
#-----
# An example using a HDF5Array-backed BSseq object
#
```

```
library(HDF5Array)
hdf5_M <- realize(M, "HDF5Array")
hdf5_Cov <- realize(Cov, "HDF5Array")
hdf5_BS1 <- BSseq(chr = c("chr1", "chr2", "chr1"),
                 pos = c(1, 2, 3),
                 M = hdf5_M,
                 Cov = hdf5_Cov,
                 sampleNames = c("A", "B", "C"))
hdf5_BS1
hdf5_BS2 <- BSseq(chr = c("chr1", "chr1", "chr1"),
                 pos = c(1, 1, 1),
                 M = hdf5_M,
                 Cov = hdf5_Cov,
                 sampleNames = c("A", "B", "C"))
hdf5_BS2
```

---

BSseq-class

*Class BSseq*

---

**Description**

A class for representing whole-genome or capture bisulfite sequencing data.

## Objects from the Class

An object from the class links together several pieces of information. (1) genomic locations stored as a GRanges object, a location by samples matrix of M values, a location by samples matrix of Cov (coverage) values and phenodata information. In addition, there are slots for representing smoothed data. This class is an extension of [RangedSummarizedExperiment](#).

## Slots

**trans:** Object of class function. This function transforms the coef slot from the scale the smoothing was done to the 0-1 methylation scale.

**parameters:** Object of class list. A list of parameters representing for example how the data was smoothed.

## Methods

[ signature(x = "BSseq"): Subsetting by location (using integer indices) or sample (using integers or sample names).

**length** Unlike for RangedSummarizedExperiment, length() is the number of methylation loci (equal to length(granges(x))).

**sampleNames, sampleNames<-** Sample names and its replacement function for the object. This is an alias for colnames.

**pData, pData<-** Obtain and replace the pData slot of the phenoData slot. This is an alias for colData.

**show** The show method.

**combine** This function combines two BSseq objects. The genomic locations of the new object is the union of the genomic locations of the individual objects. In addition, the methylation data matrices are placed next to each other (as appropriate wrt. the new genomic locations) and zeros are entered into the matrices as needed.

## Utilities

This class extends [RangedSummarizedExperiment](#) and therefore inherits a number of useful GRanges methods that operate on the rowRanges slot, used for accessing and setting the genomic locations and also do subsetByOverlaps.

There are a number of almost methods-like functions for operating on objects of class BSseq, including getBSseq, collapseBSseq, and orderBSseq. They are detailed below.

collapseBSseq(BSseq, columns) is used to collapse an object of class BSseq. By collapsing we simply mean that certain columns (samples) are merge together by summing up the methylation evidence and coverage. This is a useful function if you start by reading in a dataset based on say flowcells and you (after QC) want to simply add a number of flowcells into one sample. The argument columns specify which samples are to be merged, in the following way: it is a character vector of new sample names, and the names of the column vector indicates which samples in the BSseq object are to be collapsed. If columns have the same length as the number of rows of BSseq (and has no names) it is assumed that the ordering corresponds to the sample ordering in BSseq.

`orderBSseq(BSseq, seqOrder = NULL)` simply orders an object of class `BSseq` according to (increasing) genomic locations. The `seqOrder` vector is a character vector of `seqnames(BSseq)` describing the order of the chromosomes. This is useful for ordering `chr1` before `chr10`.

`chrSelectBSseq(BSseq, seqnames = NULL, order = FALSE)` subsets and optionally reorders an object of class `BSseq`. The `seqnames` vector is a character vector of `seqnames(BSseq)` describing which chromosomes should be retained. If `order` is `TRUE`, the chromosomes are also re-ordered using `orderBSseq`.

`getBSseq(BSseq, type = c("Cov", "M", "gr", "coef", "se.coef", "trans", "parameters"))` is a general accessor: is used to obtain a specific slot of an object of class `BSseq`. It is primarily intended for internal use in the package, for users we recommend `granges` to get the genomic locations, `getCoverage` to get the coverage slots and `getMeth` to get the smoothed values (if they exist).

`hasBeenSmoothed(BSseq)` This function returns a logical depending on whether or not the `BSseq` object has been smoothed using `BSmooth`.

`combineList(list, BACKEND = NULL)` This function is a faster way of using `combine` on multiple `BSseq` objects. The input is a list, with each component an object of class `BSseq`. The (slower) alternative is to use `Reduce(combine, list)`.

The `BACKEND` argument determines which backend should be used for the 'M' and 'Cov' matrices and, if present, the 'coef' and 'se.coef' matrices (the latter two can only be combined if all objects have the same `rowRanges`). The default, `BACKEND = NULL`, corresponds to using `matrix` objects. See `?DelayedArray::setAutoRealizationBackend` for alternative backends.

`strandCollapse(BSseq, shift = TRUE)` This function operates on a `BSseq` objects which has stranded loci (i.e. loci where the strand is one of '+' or '-'). It will collapse the methylation and coverage information across the two strands, unstranding the loci in the process and potentially re-ordering them.

The argument `shift` indicates whether the positions for the loci on the reverse strand should be shifted one (i.e. the positions for these loci are the positions of the 'G' in the 'CpG'; this is the case for Bismark output for example).

## Coercion

Package versions 1.5.2 and 1.11.1 introduced a new version of representing 'BSseq' objects. You can update old serialized (saved) objects by invoking `x <-updateObject(x)`.

## Assays

This class overrides the default implementation of assays to make it faster. Per default, no names are added to the returned data matrices.

Assay names can conveniently be obtained by the function `assayNames(x)`

## Author(s)

Kasper Daniel Hansen <khansen@jhsp.h.harvard.edu>

**See Also**

The package vignette. [BSseq](#) for the constructor function. [RangedSummarizedExperiment](#) for the underlying class. [getBSseq](#), [getCoverage](#), and [getMeth](#) for accessing the data stored in the object and finally [BSmooth](#) for smoothing the bisulfite sequence data.

**Examples**

```
M <- matrix(1:9, 3,3)
colnames(M) <- c("A1", "A2", "A3")
BStest <- BSseq(pos = 1:3, chr = c("chr1", "chr2", "chr1"), M = M, Cov = M + 2)
chrSelectBSseq(BStest, seqnames = "chr1", order = TRUE)
collapseBSseq(BStest, group = c("A", "A", "B"))

#-----
# An example using a HDF5-backed BSseq object
#
hdf5_BStest <- realize(BStest, "HDF5Array")
chrSelectBSseq(hdf5_BStest, seqnames = "chr1", order = TRUE)
collapseBSseq(
  BSseq = hdf5_BStest,
  group = c("A", "A", "B"),
  BACKEND = "HDF5Array",
  type = "integer")
```

BSseqStat-class

*Class BSseqStat***Description**

A class for representing statistics for smoothed whole-genome bisulfite sequencing data.

**Usage**

```
BSseqStat(gr = NULL, stats = NULL, parameters = NULL)
```

**Arguments**

<code>gr</code>	The genomic locations as an object of class <code>GRanges</code> .
<code>stats</code>	The statistics, as a list of matrix-like objects (see 'Details' below).
<code>parameters</code>	A list of parameters.

**Details**

The matrix-like elements of the list in the 'stats' slot will be coerced to [DelayedMatrix](#) objects; see `?DelayedArray::DelayedMatrix` for the full list of supported matrix-like objects. We recommend using [matrix](#) objects for in-memory storage of data and [HDF5Matrix](#) for on-disk storage of data.

### Objects from the Class

Objects can be created by calls of the form `BSseqStat(...)`. However, usually objects are returned by `BSmooth.fstat(...)` and not constructed by the user.

### Slots

**stats:** This is a list of [DelayedMatrix](#) objects with list elements representing various statistics for methylation loci along the genome.

**parameters:** Object of class `list`. A list of parameters representing how the statistics were computed.

**gr:** Object of class `GRanges` giving genomic locations.

### Extends

Class [hasGRanges](#), directly.

### Methods

[ The subsetting operator; one may only subset in one dimension, corresponding to methylation loci.

**show** The show method.

### Utilities

This class extends `hasGRanges` and therefore inherits a number of useful `GRanges` methods that operate on the `gr` slot, used for accessing and setting the genomic locations and also do `subsetByOverlaps`.

### Coercion

Package version 1.11.1 introduced a new version of representing 'BSseqStat' objects. You can update old serialized (saved) objects by invoking `x <-updateObject(x)`.

### Author(s)

Kasper Daniel Hansen <[khansen@jhsph.edu](mailto:khansen@jhsph.edu)>

### See Also

[hasGRanges](#) for accessing the genomic locations. [BSmooth.fstat](#) for a function that returns objects of class `BSseqStat`, and [smoothSds](#), [computeStat](#) and [dmrFinder](#) for functions that operate based on these statistics. Also see the more specialised [BSseqTstat](#).

---

BSseqTstat-class	<i>Class BSseqTstat</i>
------------------	-------------------------

---

### Description

A class for representing t-statistics for smoothed whole-genome bisulfite sequencing data.

### Usage

```
BSseqTstat(gr = NULL, stats = NULL, parameters = NULL)
```

### Arguments

<code>gr</code>	The genomic locations as an object of class GRanges.
<code>stats</code>	The statistics, as a matrix-like object (see 'Details' below).
<code>parameters</code>	A list of parameters.

### Details

The 'stats' matrix-like object will be coerced to a [DelayedMatrix](#) object; see `?DelayedArray::DelayedMatrix` for the full list of supported matrix-like objects. We recommend using [matrix](#) objects for in-memory storage of data and [HDF5Matrix](#) for on-disk storage of data.

### Objects from the Class

Objects can be created by calls of the form `BSseqTstat(...)`. However, usually objects are returned by `BSmooth.tstat(...)` and not constructed by the user.

### Slots

`stats`: This is a [DelayedMatrix](#) object with columns representing various statistics for methylation loci along the genome.

`parameters`: Object of class `list`. A list of parameters representing how the t-statistics were computed.

`gr`: Object of class GRanges giving genomic locations.

### Extends

Class [hasGRanges](#), directly.

### Methods

[ The subsetting operator; one may only subset in one dimension, corresponding to methylation loci.

`show` The show method.

**Utilities**

This class extends `hasGRanges` and therefore inherits a number of useful `GRanges` methods that operate on the `gr` slot, used for accessing and setting the genomic locations and also do `subsetByOverlaps`.

**Coercion**

Package version 1.11.1 introduced a new version of representing ‘`BSseqTstat`’ objects. You can update old serialized (saved) objects by invoking `x <-updateObject(x)`.

**Author(s)**

Kasper Daniel Hansen <khansen@jhsp.h.harvard.edu>

**See Also**

The package vignette(s). [hasGRanges](#) for accessing the genomic locations. [BSmooth.tstat](#) for a function that returns objects of class `BSseqTstat`, and [dmrFinder](#) for a function that computes DMRs based on the t-statistics. Also see [BS.cancer.ex.tstat](#) for an example of the class in the `bsseqData` package.

---

`data.frame2GRanges`      *Converts a data frame to a GRanges.*

---

**Description**

Converting a `data.frame` to a `GRanges` object. The `data.frame` needs columns like `chr`, `start` and `end` (`strand` is optional). Additional columns may be kept in the `GRanges` object.

**Usage**

```
data.frame2GRanges(df, keepColumns = FALSE, ignoreStrand = FALSE)
```

**Arguments**

<code>df</code>	A <code>data.frame</code> with columns <code>chr</code> or <code>seqnames</code> , <code>start</code> , <code>end</code> and optionally a <code>strand</code> column.
<code>keepColumns</code>	In case <code>df</code> has additional columns, should these columns be stored as metadata columns on the return <code>GRanges</code> or should they be discarded.
<code>ignoreStrand</code>	In case <code>df</code> has a <code>strand</code> column, should this column be ignored.

**Value**

An object of class `GRanges`

**Note**

In case `df` has `rownames`, they will be used as names for the return object.



**Author(s)**

Kasper Daniel Hansen <khansen@jhsp.h.edu>

**Examples**

```
df <- data.frame(chr = "chr1", start = 1:3, end = 2:4,
                 strand = c("+", "-", "+"))
data.frame2GRanges(df, ignoreStrand = TRUE)
```

---

dmrFinder	<i>Finds differentially methylated regions for whole genome bisulfite sequencing data.</i>
-----------	--

---

**Description**

Finds differentially methylated regions for whole genome bisulfite sequencing data. Essentially identifies regions of the genome where all methylation loci have an associated t-statistic that is beyond a (low, high) cutoff.

**Usage**

```
dmrFinder(bstat, cutoff = NULL, qcutoff = c(0.025, 0.975),
          maxGap=300, stat = "tstat.corrected", verbose = TRUE)
```

**Arguments**

bstat	An object of class BSseqStat or BSseqTstat.
cutoff	The cutoff of the t-statistics. This should be a vector of length two giving the (low, high) cutoff. If NULL, see qcutoff.
qcutoff	In case cutoff is NULL, compute the cutoff using these quantiles of the t-statistic.
maxGap	If two methylation loci are separated by this distance, break a possible DMR. This guarantees that the return DMRs have CpGs that are this distance from each other.
stat	Which statistic should be used?
verbose	Should the function be verbose?

**Details**

The workhorse function is BSmooth.tstat which sets up a t-statistic for a comparison between two groups.

Note that post-processing of these DMRs are likely to be necessary, filtering for example for length (or number of loci).

**Value**

A data.frame with columns

start,end,width,chr	genomic locations and width.
n	The number of methylation loci.
invdensity	Average length per loci.
group1.mean	The mean methylation level across samples and loci in 'group1'.
group2.mean	The mean methylation level across samples and loci in 'group2'.
meanDiff	The mean difference in methylation level; the difference between group1.mean and group2.mean.
idxStart, idxEnd, cluster	Internal use.
areaStat	The 'area' of the t-statistic; equal to the sum of the t-statistics for the individual methylation loci.
direction	either 'hyper' or 'hypo'.
areaStat.corrected	Only present if column = "tstat.corrected", contains the area of the corrected t-statistics.

**Author(s)**

Kasper Daniel Hansen <khansen@jhsp.h.harvard.edu>.

**References**

KD Hansen, B Langmead, and RA Irizarry. *BSmooth: from whole genome bisulfite sequencing reads to differentially methylated regions*. Genome Biology (2012) 13:R83. doi:[10.1186/gb-2012-13-10-r83](https://doi.org/10.1186/gb-2012-13-10-r83).

**See Also**

[BSmooth.tstat](#) for the function constructing the input object, and [BSseqTstat](#) for its class. In the example below, we use [BS.cancer.ex.tstat](#) as the actual input object. Also see the package vignette(s) for a detailed example.

**Examples**

```
if(require(bsseqData)) {
  dmrs0 <- dmrFinder(BS.cancer.ex.tstat, cutoff = c(-4.6, 4.6), verbose = TRUE)
  dmrs <- subset(dmrs0, abs(meanDiff) > 0.1 & n >= 3)
}
```

---

findLoci	<i>Find methylation loci in a genome</i>
----------	--

---

### Description

This is a convenience function to find methylation loci, such as CpGs, in a reference genome. The result is useful as the value of the loci argument for `read.bismark()`.

### Usage

```
findLoci(pattern,
         subject,
         include = seqlevels(subject),
         strand = c("*", "+", "-"),
         fixed = "subject",
         resize = TRUE)
```

### Arguments

pattern	A string specifying the pattern to search for, e.g. "CG". Can contain IUPAC ambiguity codes, e.g., "CH".
subject	A string containing a file path to the genome sequence, in FASTA or 2bit format, to be searched. Alternatively, a <a href="#">BSgenome</a> or <a href="#">DNAStringSet</a> object storing the genome sequence to be searched.
include	A character vector indicating the seqlevels of subject to be used.
strand	A character scalar specifying the strand of subject to be used. If strand = "*", then both the positive (strand = "+") and negative (strand = "-" strands will be searched.) It is assumed that subject contains the sequence with respect to the + strand.
fixed	If "subject" (the default), IUPAC ambiguity codes in the pattern only are interpreted as wildcards, e.g., a pattern containing CH matches a subject containing CA but not vice versa. See <code>?Biostrings::`lowlevel-matching`</code> for more information
resize	A logical scalar specifying whether the ranges should be shifted to have width 1 and anchored by the start of the locus, e.g., resize a CpG dinucleotide to give the co-ordinates of the cytosine.

### Details

This function provides a convenience wrapper for finding methylation loci in a genome, based on running `vmatchPattern()`. Users requiring finer-grained control should directly use the `vmatchPattern()` function and coerce the result to a [GRanges](#) object.

### Value

A [GRanges](#) object storing the found loci.

**Author(s)**

Peter F. Hickey

**See Also**

- Biostrings::vmatchPattern()
- ?BSgenome::`BSgenome-utils`

**Examples**

```
library(Biostrings)
# Find CpG dinucleotides on the both strands of an artificial sequence
my_seq <- DNASTringSet("ATCAGTCGC")
names(my_seq) <- "test"
findLoci(pattern = "CG", subject = my_seq)
# Find CHG trinucleotides on the both strands of an artificial sequence
findLoci(pattern = "CHG", subject = my_seq)

# Find CpG dinucleotides on the + strand of chr17 from the human genome (hg38)
if (requireNamespace("BSgenome.Hsapiens.UCSC.hg38")) {
  findLoci(
    pattern = "CG",
    subject = BSgenome.Hsapiens.UCSC.hg38::BSgenome.Hsapiens.UCSC.hg38,
    include = "chr17",
    strand = "+")
}
```

fisherTests

*Compute Fisher-tests for a BSseq object***Description**

A function to compute Fisher-tests for an object of class BSseq.

**Usage**

```
fisherTests(BSseq, group1, group2, lookup = NULL,
  returnLookup = TRUE, mc.cores = 1, verbose = TRUE)
```

**Arguments**

BSseq	An object of class BSseq.
group1	A vector of sample names or indexes for the ‘treatment’ group.
group2	A vector of sample names or indexes for the ‘control’ group.
lookup	A ‘lookup’ object, see details.
returnLookup	Should a ‘lookup’ object be returned, see details.
mc.cores	The number of cores used. Note that setting mc.cores to a value greater than 1 is not supported on MS Windows, see the help page for mclapply.
verbose	Should the function be verbose.

## Details

This function computes row-wise Fisher's exact tests. It uses an internal lookup table so rows which forms equivalent 2x2 tables are group together and only a single test is computed. If `returnLookup` is TRUE the return object contains the lookup table which may be feed to another call to the function using the `lookup` argument.

If `group1`, `group2` designates more than 1 sample, the samples are added together before testing.

This function can use multiple cores on the same computer.

This test cannot model biological variability.

## Value

if `returnLookup` is TRUE, a list with components `results` and `lookup`, otherwise just the `results` component. The `results` (component) is a matrix with the same number of rows as the `BSseq` argument and 2 columns `p.value` (the unadjusted p-values) and `log2OR` (log2 transformation of the odds ratio).

## Author(s)

Kasper Daniel Hansen <khansen@jhsp.h.edu>

## See Also

[fisher.test](#) for information about Fisher's test. [mclapply](#) for the `mc.cores` argument.

## Examples

```
M <- matrix(1:9, 3,3)
colnames(M) <- c("A1", "A2", "A3")
BStest <- BSseq(pos = 1:3, chr = c("chr1", "chr2", "chr1"),
               M = M, Cov = M + 2)
results <- fisherTests(BStest, group1 = "A1", group2 = "A2",
                      returnLookup = TRUE)
results

#-----
# An example using a HDF5Array-backed BSseq object
#
library(HDF5Array)
# See ?SummarizedExperiment::saveHDF5SummarizedExperiment for details
hdf5_BStest <- saveHDF5SummarizedExperiment(x = BStest,
                                           dir = tempfile())

results <- fisherTests(hdf5_BStest,
                      group1 = "A1",
                      group2 = "A2",
                      returnLookup = TRUE)
results
```

---

FWGRanges-class	<i>Classes FWIRanges and FWGRanges</i>
-----------------	--

---

**Description**

Classes for fixed-width IRanges and GRanges, ie. objects where all ranges have the same width. The intention is for these classes to be added to GenomicRanges. Documented here temporarily.

**Details**

See description. Otherwise works like IRanges and GRanges, except there are many unimplemented methods.

This is really a private class, with private methods, but R's NAMESPACE handling means they get unintentionally exported. Hence this documentation.

**Examples**

```
showClass("FWIRanges")
```

---

getCoverage	<i>Obtain coverage for BSseq objects.</i>
-------------	---

---

**Description**

Obtain coverage for BSseq objects.

**Usage**

```
getCoverage(BSseq, regions = NULL, type = c("Cov", "M"),
  what = c("perBase", "perRegionAverage", "perRegionTotal"),
  withDimnames = TRUE)
```

**Arguments**

BSseq	An object of class BSseq.
regions	An optional data.frame or GenomicRanges object specifying a number of genomic regions.
type	This returns either coverage or the total evidence for methylation at the loci.
what	The type of return object, see details.
withDimnames	A logical(1), indicating whether dimnames should be applied to extracted coverage elements. Setting withDimnames = FALSE increases the speed and memory efficiency with which coverage is extracted.

**Value**

**NOTE:** The return type of `getCoverage` varies depending on its arguments.

If regions are not specified (`regions = NULL`) a [DelayedMatrix](#) object (what = "perBase") is returned. This will either contain the per-base coverage, the average coverage, or the genome total coverage (depending on value of what).

If what = "perBase" and regions are specified, a list is returned. Each element of the list is a [DelayedMatrix](#) object corresponding to the genomic loci inside the region. It is conceptually the same as splitting the coverage by region.

If what = "perRegionAverage" or what = "perRegionTotal" and regions are specified the return value is a [DelayedMatrix](#) object. Each row of the [DelayedMatrix](#) corresponds to a region and contains either the average coverage or the total coverage in the region.

**Author(s)**

Kasper Daniel Hansen <khansen@jhsph.edu>.

**See Also**

[BSseq](#) for the BSseq class.

**Examples**

```
data(BS.chr22)
head(getCoverage(BS.chr22, type = "M"))
reg <- GRanges(seqnames = c("chr22", "chr22"),
  ranges = IRanges(start = c(1, 2*10^7), end = c(2*10^7 + 1, 4*10^7)))
getCoverage(BS.chr22, regions = reg, what = "perRegionAverage")
cList <- getCoverage(BS.chr22, regions = reg)
length(cList)
head(cList[[1]])

#-----
# An example using a HDF5Array-backed BSseq object
#

library(HDF5Array)
# See ?SummarizedExperiment::saveHDF5SummarizedExperiment for details
hdf5_BS.chr22 <- saveHDF5SummarizedExperiment(x = BS.chr22,
  dir = tempfile())

head(getCoverage(hdf5_BS.chr22, type = "M"))
reg <- GRanges(seqnames = c("chr22", "chr22"),
  ranges = IRanges(start = c(1, 2 * 10 ^ 7),
  end = c(2 * 10 ^ 7 + 1, 4 * 10 ^ 7)))
getCoverage(hdf5_BS.chr22, regions = reg, what = "perRegionAverage")
hdf5_cList <- getCoverage(hdf5_BS.chr22, regions = reg)
length(hdf5_cList)
head(hdf5_cList[[1]])
```

---

getMeth	<i>Obtain methylation estimates for BSseq objects.</i>
---------	--

---

### Description

Obtain methylation estimates for BSseq objects, both smoothed and raw.

### Usage

```
getMeth(BSseq, regions = NULL, type = c("smooth", "raw"),
        what = c("perBase", "perRegion"), confint = FALSE, alpha = 0.95,
        withDimnames = TRUE)
```

### Arguments

BSseq	An object of class BSseq.
regions	An optional data.frame or GenomicRanges object specifying a number of genomic regions.
type	This returns either smoothed or raw estimates of the methylation level.
what	The type of return object, see details.
confint	Should a confidence interval be return for the methylation estimates (see below). This is only supported if what is equal to perBase.
alpha	alpha value for the confidence interval.
withDimnames	A logical(1), indicating whether dimnames should be applied to extracted coverage elements. Setting withDimnames = FALSE increases the speed and memory efficiency with which coverage is extracted.

### Value

**NOTE:** The return type of getMeth varies depending on its arguments.

If region = NULL the what argument is ignored. This is also the only situation in which confint = TRUE is supported. The return value is either a [DelayedMatrix](#) (confint = FALSE) or a list with three [DelayedMatrix](#) components (confint = TRUE) (meth, upper and lower), giving the methylation estimates and (optionally) confidence intervals.

Confidence intervals for type = "smooth" is based on standard errors from the smoothing algorithm (if present). Otherwise it is based on pointwise confidence intervals for binomial distributions described in Agresti (see below), specifically the score confidence interval.

If regions are specified, what = "perBase" will make the function return a list, each element of the list being a [DelayedMatrix](#) corresponding to a genomic region (and each row of the [DelayedMatrix](#) being a loci inside the region). If what = "perRegion" the function returns a [DelayedMatrix](#), with each row corresponding to a region and containing the average methylation level in that region.

### Note

A BSseq object needs to be smoothed by the function BSmooth in order to support type = "smooth".



**Author(s)**

Kasper Daniel Hansen <khansen@jhsph.edu>.

**References**

A Agresti and B Coull. *Approximate Is Better than "Exact" for Interval Estimation of Binomial Proportions*. The American Statistician (1998) 52:119-126.

**See Also**

[BSseq](#) for the BSseq class and [BSmooth](#) for smoothing such an object.

**Examples**

```
data(BS.chr22)
head(getMeth(BS.chr22, type = "raw"))
reg <- GRanges(seqnames = c("chr22", "chr22"),
  ranges = IRanges(start = c(1, 2*10^7), end = c(2*10^7 + 1, 4*10^7)))
head(getMeth(BS.chr22, regions = reg, type = "raw", what = "perBase"))

#-----
# An example using a HDF5Array-backed BSseq object
#

library(HDF5Array)
# See ?SummarizedExperiment::saveHDF5SummarizedExperiment for details
hdf5_BS.chr22 <- saveHDF5SummarizedExperiment(x = BS.chr22,
  dir = tempfile())

head(getMeth(hdf5_BS.chr22, type = "raw"))
head(getMeth(hdf5_BS.chr22, regions = reg, type = "raw", what = "perBase"))
```

---

getStats

*Obtain statistics from a BSseqTstat object*

---

**Description**

Essentially an accessor function for the statistics of a BSseqTstat object.

**Usage**

```
getStats(bstat, regions = NULL, ...)
```

**Arguments**

bstat	An object of class BSseqStat or BSseqTstat.
regions	An optional data.frame or GenomicRanges object specifying a number of genomic regions.
...	Additional arguments passed to the different backends based on the class of bstat; see Details.

### Details

Additional argument when the `bstat` object is of class `BSseqTstat`:

**stat** Which statistics column should be obtained.

### Value

An object of class `data.frame` possible restricted to the regions specified.

### Author(s)

Kasper Daniel Hansen <khansen@jhsp.h.edu>

### See Also

[BSseqTstat](#) for the `BSseqTstat` class, and [getCoverage](#) and [getMeth](#) for similar functions, operating on objects of class `BSseq`.

### Examples

```
if(require(bsseqData)) {
  data(BS.cancer.ex.tstat)
  head(getStats(BS.cancer.ex.tstat))
  reg <- GRanges(seqnames = c("chr22", "chr22"),
    ranges = IRanges(start = c(1, 2*10^7), end = c(2*10^7 + 1, 4*10^7)))
  head(getStats(BS.cancer.ex.tstat, regions = reg))
}
```

---

GoodnessOfFit

*Binomial and poisson goodness of fit statistics for BSseq objects*

---

### Description

Binomial and poisson goodness of fit statistics for `BSseq` objects, including plotting capability.

### Usage

```
poissonGoodnessOfFit(BSseq, nQuantiles = 10^5)
binomialGoodnessOfFit(BSseq, method = c("MLE"), nQuantiles = 10^5)
## S3 method for class 'chisqGoodnessOfFit'
print(x, ...)
## S3 method for class 'chisqGoodnessOfFit'
plot(x, type = c("chisq", "pvalue"), plotCol = TRUE, qqline = TRUE,
  pch = 16, cex = 0.75, ...)
```

**Arguments**

BSseq	An object of class BSseq.
x	A chisqGoodnessOfFit object (as produced by poissonGoodnessOfFit or binomialGoodnessOfFit).
nQuantiles	The number of (evenly-spaced) quantiles stored in the return object.
method	How is the parameter estimated.
type	Are the chisq or the p-values being plotted.
plotCol	Should the extreme quantiles be colored.
qqline	Add a qqline.
pch, cex	Plotting symbols and size.
...	Additional arguments being passed to qqplot (for plot) or ignored (for print).

**Details**

These functions compute and plot goodness of fit statistics for BSseq objects. For each methylation loci, the Poisson goodness of fit statistic tests whether the coverage (at that loci) is independent and identically Poisson distributed across the samples. In a similar fashion, the Binomial goodness of fit statistic tests whether the number of reads supporting methylation are independent and identically binomial distributed across samples (with different size parameters given by the coverage vector).

These functions do not handle NA values.

**Value**

The plotting method is invoked for its side effect. Both poissonGoodnessOfFit and binomialGoodnessOfFit returns an object of class chisqGoodnessOfFit which is a list with components

chisq	a vector of Chisq values.
quantiles	a vector of quantiles (of the chisq values).
df	degrees of freedom

**Author(s)**

Kasper Daniel Hansen <khansen@jhsp.h.harvard.edu>

**See Also**

For the plotting method, see qqplot.

**Examples**

```
if(require(bsseqData)) {
  data(BS.cancer.ex)
  BS.cancer.ex <- updateObject(BS.cancer.ex)
  gof <- poissonGoodnessOfFit(BS.cancer.ex)
  plot(gof)

#-----
# An example using a HDF5Array-backed BSseq object
```

```

#
library(HDF5Array)

# See ?SummarizedExperiment::saveHDF5SummarizedExperiment for details
hdf5_BS.cancer.ex <- saveHDF5SummarizedExperiment(x = BS.cancer.ex,
                                                  dir = tempfile())
hdf5_gof <- poissonGoodnessOfFit(hdf5_BS.cancer.ex)
plot(hdf5_gof)
}

```

---

hasGRanges-class      *Class hasGRanges*

---

### Description

A class with a GRanges slot, used as a building block for other classes. Provides basic accessor functions etc.

### Objects from the Class

Objects can be created by calls of the form `new("hasGRanges", ...)`.

### Slots

**gr**: Object of class GRanges.

### Methods

**"["** Subsets a single dimension.

**granges** Get the GRanges object representing genomic locations.

**start,start<-,end,end<-,width,width<-** Start, end and width for the genomic locations of the object, also replacement functions. This accessor functions operate directly on the gr slot.

**strand,strand<-** Getting and setting the strand of the genomic locations (the gr slot).

**seqlengths,seqlengths<-** Getting and setting the seqlengths of the genomic locations (the gr slot).

**seqlevels,seqlevels<-** Getting and setting the seqlevels of the genomic locations (the gr slot).

**seqnames,seqnames<-** Getting and setting the seqnames of the genomic locations (the gr slot).

**show** The show method.

**findOverlaps** (query = "hasGRanges", subject = "hasGRanges"): finds overlaps between the `granges()` of the two objects.

**findOverlaps** (query = "GenomicRanges", subject = "hasGRanges"): finds overlaps between query and the `granges()` of the subject.

- findOverlaps** (query = "hasGRanges", subject = "GenomicRanges"): finds overlaps between the `granges()` of the query and the subject.
- subsetByOverlaps** (query = "hasGRanges", subject = "hasGRanges"): Subset the query, keeping the genomic locations that overlaps the subject.
- subsetByOverlaps** (query = "hasGRanges", subject = "GenomicRanges"): Subset the query, keeping the genomic locations that overlaps the subject.
- subsetByOverlaps** (query = "GenomicRanges", subject = "hasGRanges"): Subset the query, keeping the genomic locations that overlaps the subject.

### Note

If you extend the `hasGRanges` class, you should consider writing a `subset` method (`[]`), and a `show` method. If the new class supports single index subsetting, the `subsetByOverlaps` methods will automatically extend.

### Author(s)

Kasper Daniel Hansen <khansen@jhsph.edu>

### Examples

```
showClass("hasGRanges")
```

---

plotRegion

*Plotting BSmooth methylation estimates*

---

### Description

Functions for plotting BSmooth methylation estimates. Typically used to display differentially methylated regions.

### Usage

```
plotRegion(BSseq, region = NULL, extend = 0, main = "",
  addRegions = NULL, annoTrack = NULL, cex.anno = 1,
  geneTrack = NULL, cex.gene = 1.5, col = NULL, lty = NULL,
  lwd = NULL, BSseqStat = NULL, stat = "tstat.corrected",
  stat.col = "black", stat.lwd = 1, stat.lty = 1, stat.ylim = c(-8, 8),
  mainWithWidth = TRUE, regionCol = alpha("red", 0.1), addTicks = TRUE,
  addPoints = FALSE, pointsMinCov = 5, highlightMain = FALSE)
```

```
plotManyRegions(BSseq, regions = NULL, extend = 0, main = "",
  addRegions = NULL, annoTrack = NULL, cex.anno = 1,
  geneTrack = NULL, cex.gene = 1.5, col = NULL, lty = NULL,
  lwd = NULL, BSseqStat = NULL, stat = "tstat.corrected",
  stat.col = "black", stat.lwd = 1, stat.lty = 1, stat.ylim = c(-8, 8),
  mainWithWidth = TRUE, regionCol = alpha("red", 0.1), addTicks = TRUE,
  addPoints = FALSE, pointsMinCov = 5, highlightMain = FALSE,
  verbose = TRUE)
```

**Arguments**

BSseq	An object of class BSseq.
region	A data.frame (with start, end and chr columns) with 1 row or GRanges of length 1. If region is NULL the entire BSseq argument is plotted.
regions	A data.frame (with start, end and chr columns) or GRanges.
extend	Describes how much the plotting region should be extended in either direction. The total width of the plot is equal to the width of the region plus twice extend.
main	The plot title. The default is to construct a title with information about which genomic region is being plotted.
addRegions	A set of additional regions to be highlighted on the plots. As the regions argument.
annoTrack	A named list of GRanges objects. Each component is a track and the names of the list are the track names. Each track will be plotted as solid bars, and we routinely display information such as CpG islands, exons, etc.
cex.anno	cex argument when plotting annoTrack.
geneTrack	<b>EXPERIMENTAL:</b> A data.frame with columns: chr, start, end, gene_ID, exon_number, strand, gene_name, isoforms. This interface is under active development and subject to change.
cex.gene	cex argument when plotting geneTrack.
col	The color of the methylation estimates, see details.
lty	The line type of the methylation estimates, see details.
lwd	The line width of the methylation estimates, see details.
BSseqStat	An object of class BSseqStat. If present, a new panel will be shown with the t-statistics.
stat	Which statistics will be plotted (only used if BSseqStat is not NULL.)
stat.col	color for the statistics plot.
stat.lwd	line width for the statistics plot.
stat.lty	line type for the statistics plot.
stat.ylim	y-limits for the statistics plot.
mainWithWidth	Should the default title include information about width of the plot region.
regionCol	The color used for highlighting the region.
addTicks	Should tick marks showing the location of methylation loci, be added?
addPoints	Should the individual unsmoothed methylation estimates be plotted. This usually leads to a very confusing plot, but may be useful for diagnostic purposes.
pointsMinCov	The minimum coverage a methylation loci need in order for the raw methylation estimates to be plotted. Useful for filtering out low coverage loci. Only used if addPoints = TRUE.
highlightMain	Should the plot region be highlighted?
verbose	Should the function be verbose?

**Details**

The correct choice of aspect ratio depends on the width of the plotting region. We tend to use `width = 10, height = 5`.

`plotManyRegions` is used to plot many regions (hundreds or thousands), and is substantially quicker than repeated calls to `plotRegion`.

This function has grown to be rather complicated over time. For custom plotting, it is sometimes useful to use the function definition as a skeleton and directly modify the code.

**Value**

This function is invoked for its side effect: producing a plot.

**Author(s)**

Kasper Daniel Hansen <khansen@jhsp.h.edu>

**See Also**

The package vignette has an extended example.

---

`read.bismark`*Parsing output from the Bismark alignment suite.*

---

**Description**

Parsing output from the Bismark alignment suite.

**Usage**

```
read.bismark(files,
             loci = NULL,
             colData = NULL,
             rmZeroCov = FALSE,
             strandCollapse = TRUE,
             BPPARAM = bpparam(),
             BACKEND = NULL,
             dir = tempfile("BSseq"),
             replace = FALSE,
             chunkdim = NULL,
             level = NULL,
             nThread = 1L,
             verbose = getOption("verbose"))
```

**Arguments**

files	The path to the files created by running Bismark's methylation extractor, one sample per file. Files ending in .gz or .bz2 will be automatically decompressed to <code>tempfile()</code> . We strongly recommend you use the 'genome wide cytosine report' output files. See section 'File formats' for further details.
loci	NULL (default) or a <a href="#">GenomicRanges</a> instance containing methylation loci (all with width equal to 1). If loci = NULL, then <code>read.bismark()</code> will perform a first pass over the Bismark file to identify candidate loci. If loci is a <a href="#">GenomicRanges</a> instance, then these form the candidate loci. In either case, the candidate loci will be filtered if <code>rmZeroCov = TRUE</code> and collapsed if <code>strandCollapse = TRUE</code> to form the final set of methylation loci that form the <a href="#">rowRanges</a> of the returned <a href="#">BSseq</a> object. See section 'Efficient use of <code>read.bismark()</code> ' for further details.
colData	An optional <a href="#">DataFrame</a> describing the samples. Row names, if present, become the column names of the <a href="#">BSseq</a> object. If NULL, then a <a href="#">DataFrame</a> will be created with files used as the row names.
rmZeroCov	A <code>logical(1)</code> indicating whether methylation loci that have zero coverage in all samples be removed. For several reasons, the default <code>rmZeroCov = FALSE</code> is recommended even in cases where you ultimately want to remove such loci. See section 'Efficient use of <code>read.bismark()</code> ' for further details.
strandCollapse	A <code>logical(1)</code> indicating whether strand-symmetric methylation loci (i.e. CpGs) should be collapsed across strands. This is only applicable for stranded methylation loci, e.g., loci extracted from 'genome wide cytosine reports' (see section 'File formats' for further details).
BPPARAM	An optional <a href="#">BiocParallelParam</a> instance determining the parallel back-end to be used during evaluation. Currently supported are <a href="#">SerialParam</a> (Unix, Mac, Windows), <a href="#">MulticoreParam</a> (Unix and Mac), <a href="#">SnowParam</a> (Unix, Mac, and Windows, limited to single-machine clusters), and <a href="#">BatchJobsParam</a> (Unix, Mac, Windows, only with the in-memory realization backend). See sections 'Parallelization and progress monitoring' and 'Realization backends' for further details.
BACKEND	NULL or a single string specifying the name of the realization backend. When the backend is set to NULL, the M and Cov assays are realized in memory as ordinary matrices, otherwise these are realized with the given BACKEND. See section 'Realization backends' for further details.
dir	<b>Only applicable if</b> <code>BACKEND == "HDF5Array"</code> . The path (as a single string) to the directory where to save the HDF5-based <a href="#">BSseq</a> object. The directory will be created so should not already exist, unless <code>replace</code> is set to TRUE.
replace	<b>Only applicable if</b> <code>BACKEND == "HDF5Array"</code> . If directory <code>dir</code> already exists, should it be replaced with a new one? The content of the existing directory will be lost!
chunkdim	<b>Only applicable if</b> <code>BACKEND == "HDF5Array"</code> . The dimensions of the chunks to use for writing the data to disk. By default, <code>getHDF5DumpChunkDim()</code> using the dimensions of the returned <a href="#">BSseq</a> object will be used. See <code>?getHDF5DumpChunkDim</code> for more information.



level	<b>Only applicable if</b> <code>BACKEND == "HDF5Array"</code> . The compression level to use for writing the data to disk. By default, <code>getHDF5DumpCompressionLevel()</code> will be used. See <code>?getHDF5DumpCompressionLevel</code> for more information.
nThread	The number of threads used by <code>fread</code> when reading the files. Be careful when combining a parallel backend specified with <code>BPPARAM</code> with <code>nThread &gt; 1</code> because each worker will use <code>nThread</code> .
verbose	A <code>logical(1)</code> indicating whether progress messages should be printed (default <code>TRUE</code> ).

**Value**

A `BSseq` object.

**File formats**

The format of each file is automatically detected using the internal function `bsseq:::guessBismarkFileType()`. Files ending in `.gz`, `.bz2`, `.xz`, or `.zip` will be automatically decompressed to `tempdir()`.

**Supported file formats:** Bismark's 'genome wide cytosine report' (<https://github.com/FelixKrueger/Bismark/tree/master/Docs#the-genome-wide-cytosine-report-optional-is-tab-delimited-i>) and 'coverage' (<https://github.com/FelixKrueger/Bismark/tree/master/Docs#the-coverage-output-looks-l>) formats are both supported. If setting `loci = NULL`, then we strongly recommend using the 'genome wide cytosine report' output format because this includes strand information for each locus. The 'coverage' output does not contain strand information and so the `strand` of the returned `BSseq` object will be set to `*` unless stranded `loci` are supplied.

**Unsupported file formats:** Neither the 'bedGraph' output format (<https://github.com/FelixKrueger/Bismark/tree/master/Docs#the-bedgraph-output-optional-looks-like-this-tab-delimited->) nor the 'bismark\_methylation\_extractor' output format ([https://github.com/FelixKrueger/Bismark/tree/master/Docs#the-bismark\\_methylation\\_extractor-output-is-in-the-form-tab-delimited-1-](https://github.com/FelixKrueger/Bismark/tree/master/Docs#the-bismark_methylation_extractor-output-is-in-the-form-tab-delimited-1-)) are supported. The former does not include the required counts of methylated and unmethylated reads while the latter is an intermediate file containing read-level, rather than locus-level, data on methylation.

**One-based vs. zero-based genomic co-ordinates:** The genomic co-ordinates of the Bismark output files may be zero-based or one-based depending on whether the `--zero_based` argument was used when running Bismark's methylation extractor. Furthermore, the default co-ordinate counting system varies by version of Bismark. `bsseq` makes no assumptions about the basis of the genomic co-ordinates and it is left to the user to ensure that the appropriate basis is used in the analysis of their data.

Since Bioconductor packages typically use one-based co-ordinates, we strongly recommend that your Bismark files are also one-based.

**Efficient use of read.bismark()**

We recommend the following to achieve fast and efficient importing of Bismark files:

- Specify the set of methylation loci via the `loci` argument.
- Use Bismark files in the 'coverage' output format.

- Leave `rmZeroCov = FALSE`.
- Use a `BPPARAM` with a moderate number of workers (cores).
- Use `BACKEND = "HDF5Array"`.
- Use multiple threads per worker (i.e. `nThread > 1`).

Each point is discussed below.

**Specifying loci:** Specifying the set of methylation loci via the `loci` argument means that `read.bismark()` does not need to first parse all files to identify the set of candidate loci. Provided that `rmZeroCov = FALSE`, this means that each file is only read once. This may be a considerable saving when there are a large number of files.

**If you are unsure whether the below-described shortcuts apply to your data, leave `loci = NULL` and let `read.bismark()` identify the set of candidate loci from files.**

You may wish to use the `findLoci()` function to find all methylation loci of interest in your reference genome (e.g., all CpGs) and then pass the result via the `loci` argument.

Alternatively, if all files are 'genome wide cytosine reports' for samples aligned to the same reference genome, then all files contain the exact same set of methylation loci. In this case, you may wish to first construct `loci` using the internal function `bsseq:::readBismarkAsFWGRanges()` applied to a single file, e.g., `loci = bsseq:::readBismarkAsFWGRanges(files[1], rmZeroCov, strandCollapse)`.

**Using the 'coverage' Bismark files:** It will generally be faster to parse Bismark files in the 'coverage' output format than those in the 'genome wide cytosine report' format. This is because the former only includes loci with non-zero coverage and so the file size is often considerably smaller, particularly for shallowly sequenced samples (e.g., those from single-cell bisulfite sequencing).

**Leaving `rmZeroCov = FALSE`:** If you set `rmZeroCov = TRUE`, then `read.bismark()` must first parse all the files to identify which loci have zero coverage in all samples and then filter these out from the set of candidate loci. **This will happen even if you supply `loci` with a `GenomicRanges` of candidate loci.**

Furthermore, any coverage-based filtering of methylation loci is best left until you have constructed your final `BSseq` object. In our experience, the final `BSseq` object is often the product of combining multiple `BSseq` objects, each constructed with a separate call to `read.bismark()`. In such cases, it is premature to use `rmZeroCov = TRUE` when running each `read.bismark()`; regrettably, combining these objects will often then lead to an inefficiently stored `BSseq` object.

**Using a `BPPARAM` with a moderate number of workers (cores):** Each file can be processed on its own, so you can process in parallel as many files as you have workers. However, if using the `HDF5Array` backend, then writing to the `HDF5` file cannot be performed in parallel and so becomes the bottleneck. Nonetheless, by using a moderate number of workers (2 - 10), we can ensure there is processed data available to write to disk as soon as the current write is completed.

**Using `BACKEND = "HDF5Array"`:** By using the `HDF5Array` realization backend from `HDF5Array`, we reduce the amount of data that is kept in-memory at any one time. Once each file is parsed, the data are written to the `HDF5` file and are no longer needed in-memory. When combined with multiple workers (cores), this means that each file will only need to read and retain in-memory 1 sample's worth of data at a time.

Conversely, if you opt for all data to be in-memory (via `BACKEND = NULL`), then each worker will pass each file's data back to the main process and memory usage will steadily accumulate to often unreasonable levels.

**Using nThread > 1:** read.bismark uses `data.table::fread` to read each file, which supports threaded-parallelisation. Depending on the system, increasing nThread can achieve near-linear speed-ups in the number of threads for reading each file. Care needs to be taken when nThread > 1 is used in conjunction with a parallel backend via BPPARAM to ensure the system isn't overloaded. For example, using `BPPARAM = MulticoreParam(workers = 10)` with nThread = 4 may use up to 40 workers simultaneously.

## Realization backends

The `read.bismark()` function creates a `BSseq` object with two assays, M and Cov. The choice of *realization backend* controls whether these assays are stored in-memory as an ordinary `matrix` or on-disk as a `HDF5Array`, for example. The choice of realization backend is controlled by the `BACKEND` argument, which defaults to the current value of `DelayedArray::getAutoRealizationBackend()`.

`read.bismark()` supports the following realization backends:

- NULL (in-memory): This stores each new assay in-memory using an ordinary `matrix`.
- `HDF5Array` (on-disk): This stores each new assay on-disk in a HDF5 file using an `HDF5Matrix` from `HDF5Array`.

Please note that certain combinations of realization backend and parallelization backend are currently not supported. For example, the `HDF5Array` realization backend is currently only compatible when used with a single-machine parallelization backend (i.e. it is not compatible with a `SnowParam` that specifies an *ad hoc* cluster of **multiple** machines).

`BSmooth()` will issue an error when given such incompatible realization and parallelization backends.

Additional arguments related to the realization backend can be passed via the `...` argument. These arguments must be named and are passed to the relevant `RealizationSink` constructor. For example, the `...` argument can be used to specify the path to the HDF5 file to be used by `BSmooth()`. Please see the examples at the bottom of the page.

## Parallelization, progress monitoring, and logging

`read.bismark()` now uses the `BiocParallel` package to implement parallelization. This brings some notable improvements:

- Imported files can now be written directly to an on-disk realization backend by the worker. This dramatically reduces memory usage compared to previous versions of `bsseq` that required all results be retained in-memory.
- Parallelization is now supported on Windows through the use of a `SnowParam` object as the value of `BPPARAM`.
- Detailed and extensive job logging facilities.

All parallelization options are controlled via the `BPPARAM` argument. In general, we recommend that users combine multicore (single-machine) parallelization with an on-disk realization backend (see section, 'Realization backend'). For Unix and Mac users, this means using a `MulticoreParam`. For Windows users, this means using a single-machine `SnowParam`. Please consult the `BiocParallel` documentation to take full advantage of the more advanced features.

A useful feature of **BiocParallel** are progress bars to monitor the status of long-running jobs, such as `BSmooth()`. Progress bars are controlled via the `progressbar` argument in the `BiocParallelParam` constructor.

**BiocParallel** also supports extensive and detailed logging facilities. Please consult the **BiocParallel** documentation to take full advantage these advanced features.

### Author(s)

Peter Hickey <peter.hickey@gmail.com>

### See Also

- `read.bssmooth()` for parsing output from the `BSmooth` alignment suite.
- `read.umtab()` for parsing legacy (old) formats from the `BSmooth` alignment suite.
- `collapseBSseq()` for collapsing (aggregating) data from sample's with multiple Bismark methylation extractor files (e.g., technical replicates).

### Examples

```
# Run read.bismark() on a single sample to construct a matrix-backed BSseq
# object.
infile <- system.file("extdata/test_data.fastq_bismark.bismark.cov.gz",
                      package = "bsseq")
bsseq <- read.bismark(files = infile,
                     colData = DataFrame(row.names = "test_data"),
                     rmZeroCov = FALSE,
                     strandCollapse = FALSE,
                     verbose = TRUE)
# This is a matrix-backed BSseq object.
sapply(assays(bsseq, withDimnames = FALSE), class)
bsseq

## Not run:
# Run read.bismark() on a single sample to construct a HDF5Array-backed BSseq
# object (with data written to 'test_dir')
test_dir <- tempfile("BSseq")
bsseq <- read.bismark(files = infile,
                     colData = DataFrame(row.names = "test_data"),
                     rmZeroCov = FALSE,
                     strandCollapse = FALSE,
                     BACKEND = "HDF5Array",
                     dir = test_dir,
                     verbose = TRUE)
# This is a HDF5Array-backed BSseq object.
sapply(assays(bsseq, withDimnames = FALSE), class)
# The 'M' and 'Cov' assays are in the HDF5 file 'assays.h5' (in 'test_dir').
sapply(assays(bsseq, withDimnames = FALSE), path)

## End(Not run)
```

---

read.bsmooth	<i>Parsing output from the BSmooth alignment suite</i>
--------------	--

---

## Description

Parsing output from the BSmooth alignment suite.

## Usage

```
read.bsmooth(dirs, sampleNames = NULL, seqnames = NULL,  
             returnRaw = FALSE, qualityCutoff = 20, rmZeroCov = FALSE,  
             verbose = TRUE)
```

## Arguments

dirs	Input directories. Usually each sample is in a different directory, or perhaps each (sample, lane) is a different directory.
sampleNames	sample names, based on the order of dirs. If NULL either set to basename(dirs) (if unique) or dirs.
seqnames	The default is to read all BSmooth output files in dirs. Using this argument, it is possible to restrict this to only files with names in seqnames (apart from .cpg.tsv and optionally .gz).
returnRaw	Should the function return the complete information in the output files?
qualityCutoff	Only use evidence (methylated and unmethylated evidence) for a given methylation loci, if the base in the read has a quality greater than this cutoff.
rmZeroCov	Should methylation loci that have zero coverage in all samples be removed. This will result in a much smaller object if the data originates from (targeted) capture bisulfite sequencing.
verbose	Make the function verbose.

## Value

Either an object of class BSseq (if returnRaw = FALSE) or a list of GRanges which each component coming from a directory.

## Note

Input files can either be gzipped or not. Gzipping the input files results in much greater speed of reading (and saves space), so it is recommended.

We are working on making this function faster and less memory hungry.

## Author(s)

Kasper Daniel Hansen <khansen@jhsp.h.edu>

**See Also**

[read.umtab](#) for parsing legacy (old) formats from the BSmooth alignment suite. [collapseBSseq](#) for collapse (merging or summing) the data in two different directories.

---

read.umtab	<i>Parsing UM tab files (legacy output) containing output from the BSmooth aligner.</i>
------------	---

---

**Description**

Parsing UM tab files containing output from the bisulfite aligner Merman. This is two different legacy formats, which we keep around. These functions are likely to be deprecated in the future.

**Usage**

```
read.umtab(dirs, sampleNames = NULL, rmZeroCov = FALSE,
           pattern = NULL, keepU = c("U10", "U20", "U30", "U40"),
           keepM = c("M10", "M20", "M30", "M40"), verbose = TRUE)
```

```
read.umtab2(dirs, sampleNames = NULL, rmZeroCov = FALSE,
            readCycle = FALSE, keepFilt = FALSE,
            pattern = NULL, keepU, keepM, verbose = TRUE)
```

**Arguments**

dirs	Input directories. Usually each sample is in a different directory.
pattern	An optional pattern, see <code>list.files</code> in the base package.
sampleNames	sample names, based on the order of <code>dirs</code> .
rmZeroCov	Should methylation loci that have zero coverage in all samples be removed. This will result in a much smaller object if the data originates from (targeted) capture bisulfite sequencing.
keepU	A vector of U columns which are kept.
keepM	A vector of M columns which are kept.
readCycle	Should the cycle columns be returned?
keepFilt	Should the filter columns be returned?
verbose	Make the function verbose.

**Details**

`read.umtab2` is newer than `read.umtab` and both process output from older versions of the BSmooth alignment suite (versions older than 0.6.1). These functions are likely to be deprecated in the future. Newer output from the BSmooth alignment suite can be parsed using `read.bsmooth`.

A script using this function can be found in the `bsseqData` package, in the file `'scripts/create_BS.cancer.R'`.

**Value**

Both functions returns lists, the components are

BSdata	An object of class BSseq containing the methylation evidence.
GC	A vector of local GC content values.
Map	A vector of local mapability values.
Mcy	A matrix of the number of unique M cycles.
Ucy	A matrix of the number of unique U cycles.
chr	A vector of chromosome names.
pos	A vector of genomic positions.
M	A matrix representing methylation evidence.
U	A matrix representing un-methylation evidence.
csums	Description of 'comp2'

**Author(s)**

Kasper Daniel Hansen <khansen@jhsph.edu>

**See Also**

[read.bsmooth](#).

**Examples**

```
## Not run:
require(bsseqData)
umDir <- system.file("umtab", package = "bsseqData")
sampleNames <- list.files(umDir)
dirs <- file.path(umDir, sampleNames, "umtab")
umData <- read.umtab(dirs, sampleNames)

## End(Not run)
```

# Index

## \* classes

- BSseq-class, 10
- BSseqStat-class, 13
- BSseqTstat-class, 15
- FWGRanges-class, 22
- hasGRanges-class, 28

## \* datasets

- BS.chr22, 2
- [,BSseq-method (BSseq-class), 10
- [,BSseqStat,ANY,ANY,ANY-method (BSseqStat-class), 13
- [,BSseqStat-method (BSseqStat-class), 13
- [,BSseqTstat,ANY,ANY,ANY-method (BSseqTstat-class), 15
- [,BSseqTstat-method (BSseqTstat-class), 15
- [,hasGRanges,ANY,ANY,ANY-method (hasGRanges-class), 28
- [,hasGRanges-method (hasGRanges-class), 28
  
- assayNames,BSseq-method (BSseq-class), 10
- assays,BSseq-method (BSseq-class), 10
  
- BatchJobsParam, 4, 32
- binomialGoodnessOfFit (GoodnessOfFit), 26
- BiocParallelParam, 4, 5, 32, 36
- BS.cancer.ex.tstat, 16, 18
- BS.chr22, 2
- BSgenome, 19
- BSmooth, 3, 8, 13, 25
- BSmooth.fstat, 14
- BSmooth.tstat, 7, 16, 18
- BSseq, 4–6, 8, 9, 10, 12, 13, 23, 25, 32–35
- BSseq-class, 10
- BSseqStat (BSseqStat-class), 13
- BSseqStat-class, 13
- BSseqTstat, 8, 14, 18, 26

- BSseqTstat (BSseqTstat-class), 15
- BSseqTstat-class, 15
  
- chisqGoodnessOfFit (GoodnessOfFit), 26
- chrSelectBSseq (BSseq-class), 10
- class:hasGRanges (hasGRanges-class), 28
- collapseBSseq, 36, 38
- collapseBSseq (BSseq-class), 10
- combine,BSseq,BSseq-method (BSseq-class), 10
- combineList (BSseq-class), 10
- computeStat, 14
  
- data.frame2GRanges, 16
- DataFrame, 9, 32
- DelayedMatrix, 9, 13–15, 23, 24
- dimnames,arrayRealizationSink-method (FWGRanges-class), 22
- dmrFinder, 8, 14, 16, 17
- DNAStrngSet, 19
  
- end,FWGRanges-method (FWGRanges-class), 22
- end,FWIRanges-method (FWGRanges-class), 22
- end,hasGRanges-method (hasGRanges-class), 28
- end<- ,FWIRanges-method (FWGRanges-class), 22
- end<- ,hasGRanges-method (hasGRanges-class), 28
  
- findLoci, 19, 34
- findOverlaps,FWGRanges,FWGRanges-method (FWGRanges-class), 22
- findOverlaps,GenomicRanges,hasGRanges-method (hasGRanges-class), 28
- findOverlaps,hasGRanges,GenomicRanges-method (hasGRanges-class), 28
- findOverlaps,hasGRanges,hasGRanges-method (hasGRanges-class), 28



- fisher.test, [21](#)
- fisherTests, [20](#)
- fread, [33](#), [35](#)
- FWGRanges-class, [22](#)
- FWIRanges-class (FWGRanges-class), [22](#)
- GenomicRanges, [32](#), [34](#)
- getAutoRealizationBackend, [4](#), [35](#)
- getBSseq, [13](#)
- getBSseq (BSseq-class), [10](#)
- getCoverage, [13](#), [22](#), [26](#)
- getHDF5DumpChunkDim, [4](#), [32](#)
- getHDF5DumpCompressionLevel, [4](#), [33](#)
- getMeth, [13](#), [24](#), [26](#)
- getStats, [25](#)
- GoodnessOfFit, [26](#)
- GRanges, [9](#), [19](#)
- granges, hasGRanges-method  
(hasGRanges-class), [28](#)
- hasBeenSmoothed (BSseq-class), [10](#)
- hasGRanges, [14–16](#)
- hasGRanges (hasGRanges-class), [28](#)
- hasGRanges-class, [28](#)
- HDF5Array, [4](#), [5](#), [35](#)
- HDF5Matrix, [5](#), [9](#), [13](#), [15](#), [35](#)
- length, BSseq-method (BSseq-class), [10](#)
- length, hasGRanges-method  
(hasGRanges-class), [28](#)
- locfit, [6](#)
- matrix, [4](#), [5](#), [9](#), [12](#), [13](#), [15](#), [35](#)
- mclapply, [21](#)
- MulticoreParam, [4](#), [5](#), [32](#), [35](#)
- names, FWIRanges-method  
(FWGRanges-class), [22](#)
- names<-, FWIRanges-method  
(FWGRanges-class), [22](#)
- orderBSseq (BSseq-class), [10](#)
- overlapsAny, GenomicRanges, hasGRanges-method  
(hasGRanges-class), [28](#)
- overlapsAny, hasGRanges, GenomicRanges-method  
(hasGRanges-class), [28](#)
- overlapsAny, hasGRanges, hasGRanges-method  
(hasGRanges-class), [28](#)
- pData, BSseq-method (BSseq-class), [10](#)
- pData<-, BSseq, data.frame-method  
(BSseq-class), [10](#)
- pData<-, BSseq, DataFrame-method  
(BSseq-class), [10](#)
- plot.chisqGoodnessOfFit  
(GoodnessOfFit), [26](#)
- plotManyRegions (plotRegion), [29](#)
- plotRegion, [29](#)
- poissonGoodnessOfFit (GoodnessOfFit), [26](#)
- print.chisqGoodnessOfFit  
(GoodnessOfFit), [26](#)
- RangedSummarizedExperiment, [11](#), [13](#)
- read.bismark, [19](#), [31](#)
- read.bsmooth, [36](#), [37](#), [39](#)
- read.umtab, [36](#), [38](#), [38](#)
- read.umtab2 (read.umtab), [38](#)
- RealizationSink, [5](#), [35](#)
- rowRanges, [32](#)
- sampleNames, BSseq-method (BSseq-class),  
[10](#)
- sampleNames<-, BSseq, ANY-method  
(BSseq-class), [10](#)
- seqlengths, hasGRanges-method  
(hasGRanges-class), [28](#)
- seqlengths<-, hasGRanges-method  
(hasGRanges-class), [28](#)
- seqlevels, hasGRanges-method  
(hasGRanges-class), [28](#)
- seqlevels<-, hasGRanges-method  
(hasGRanges-class), [28](#)
- seqnames, FWGRanges-method  
(FWGRanges-class), [22](#)
- seqnames, hasGRanges-method  
(hasGRanges-class), [28](#)
- seqnames<-, hasGRanges-method  
(hasGRanges-class), [28](#)
- SerialParam, [4](#), [32](#)
- setAutoRealizationBackend, [12](#)
- show, BSseq-method (BSseq-class), [10](#)
- show, BSseqStat-method  
(BSseqStat-class), [13](#)
- show, BSseqTstat-method  
(BSseqTstat-class), [15](#)
- smoothSds, [14](#)
- SnowParam, [4](#), [5](#), [32](#), [35](#)
- start, FWGRanges-method  
(FWGRanges-class), [22](#)

start,FWIRanges-method  
    (FWGRanges-class), 22

start,hasGRanges-method  
    (hasGRanges-class), 28

start<-,FWIRanges-method  
    (FWGRanges-class), 22

start<-,hasGRanges-method  
    (hasGRanges-class), 28

strand, 33

strand,FWGRanges-method  
    (FWGRanges-class), 22

strand,hasGRanges-method  
    (hasGRanges-class), 28

strand<-,hasGRanges,ANY-method  
    (hasGRanges-class), 28

strand<-,hasGRanges-method  
    (hasGRanges-class), 28

strandCollapse (BSseq-class), 10

subsetByOverlaps,GenomicRanges,hasGRanges-method  
    (hasGRanges-class), 28

subsetByOverlaps,hasGRanges,GenomicRanges-method  
    (hasGRanges-class), 28

subsetByOverlaps,hasGRanges,hasGRanges-method  
    (hasGRanges-class), 28

  

tempdir, 33

tempfile, 32

  

updateObject,BSseq-method  
    (BSseq-class), 10

updateObject,BSseqStat-method  
    (BSseqStat-class), 13

updateObject,BSseqTstat-method  
    (BSseqTstat-class), 15

  

vmatchPattern, 19, 20

  

width,FWGRanges-method  
    (FWGRanges-class), 22

width,FWIRanges-method  
    (FWGRanges-class), 22

width,hasGRanges-method  
    (hasGRanges-class), 28

width<-,FWIRanges-method  
    (FWGRanges-class), 22

width<-,hasGRanges-method  
    (hasGRanges-class), 28