

# Package ‘ensemblVEP’

May 12, 2024

**Version** 1.46.0

**Title** R Interface to Ensembl Variant Effect Predictor

**Author** Valerie Obenchain and Lori Shepherd

**Maintainer** Bioconductor Package Maintainer <maintainer@bioconductor.org>

**Depends** methods, BiocGenerics, GenomicRanges, VariantAnnotation

**Imports** S4Vectors (>= 0.9.25), Biostrings, SummarizedExperiment,  
GenomeInfoDb, stats

**Suggests** RUnit

**Description** Query the Ensembl Variant Effect Predictor via the perl API.

**SystemRequirements** Ensembl VEP (API version 105) and the Perl modules  
DBI and DBD::mysql must be installed. See the package README  
and Ensembl installation instructions:

[http://www.ensembl.org/info/docs/tools/vep/script/vep\\_download.html#installer](http://www.ensembl.org/info/docs/tools/vep/script/vep_download.html#installer)

**License** Artistic-2.0

**LazyLoad** yes

**biocViews** Annotation, VariantAnnotation, SNP

**RoxygenNote** 7.2.2

**PackageStatus** Deprecated

**git\_url** <https://git.bioconductor.org/packages/ensemblVEP>

**git\_branch** RELEASE\_3\_19

**git\_last\_commit** 8bc30f8

**git\_last\_commit\_date** 2024-04-30

**Repository** Bioconductor 3.19

**Date/Publication** 2024-05-12

## Contents

ensemblVEP . . . . .	2
oldRuntimeOptions . . . . .	4

parseCSQToGRanges . . . . .	9
runtimeOptions . . . . .	11
VEPFlags-class . . . . .	12
VEPParam-class . . . . .	14

<b>Index</b>	<b>19</b>
--------------	-----------

---

ensemblVEP	<i>Query Ensembl Variant Effect Predictor</i>
------------	---

---

## Description

Retrieve variant annotation data from the Ensembl Variant Effect Predictor (VEP).

## Usage

```
## S4 method for signature 'character'
ensemblVEP(file, param=VEPFlags(), ..., verbose=FALSE)
```

## Arguments

file	A character specifying the full path to the file, including the file name. Valid input file types are described on the Ensembl VEP web page. <a href="http://www.ensembl.org/info/docs/variation/vep/vep_script.html#running">http://www.ensembl.org/info/docs/variation/vep/vep_script.html#running</a>
param	An instance of VEPFlags specifying runtime options.
...	Additional arguments passed to methods.
verbose	logical(1) should system call to vep be printed

## Details

- The Ensembl VEP tool is described in detail on the home page (link in ‘see also’ section). The ensemblVEP function wraps the perl API and requires a local install of the Ensembl VEP available in the user’s path. The VEPFlags class provides a way to specify runtime options. Results are returned from Ensembl VEP as GRanges (default) or VCF objects. Alternatively, results can be written directly to a file. Note: if using vep version < 90 the param is an instance of VEPParam instead of VEPFlags. The default host is not specified and therefore will use vep default of ensembl.db.ensembl.org. Users in the US may find connection and transfer speeds quicker using our East coast mirror, useast.db.ensembl.org.

## Value

Default behavior returns a GRanges object. Options can be set to return a VCF object or write a file to disk.

## Author(s)

Valerie Obenchain and Lori Shepherd

**References**

Ensembl VEP Home: <http://www.ensembl.org/info/docs/tools/vep/index.html>

Human Genome Variation Society (hgvs): <http://www.hgvs.org/mutnomen/>

**See Also**

[VEPFlags-class](#)

**Examples**

```
## -----
## Results returned as GRanges or VCF objects
## -----
## The default behavior returns a GRanges with the consequence
## data as metadata columns.
file <- system.file("extdata", "ex2.vcf", package="VariantAnnotation")
## Not run:
gr <- ensemblVEP(file)
gr[1:3]

## End(Not run)
## When the 'vcf' option is TRUE, a VCF object is returned.
myparam <- VEPFlags(flags=list(vcf=TRUE, host="useastdb.ensembl.org"))
vcf <- ensemblVEP(file, param=myparam)
vcf

## The consequence data are returned as the 'CSQ' column in info.
info(vcf)$CSQ

## To parse this column use parseCSQToGRanges().
csq <- parseCSQToGRanges(vcf)
head(csq, 4)

## The columns returned are controlled by the 'fields' option.
## By default all fields are returned. See ?VEPFlags for details.

## When comparing ensemblVEP() results to the data in the
## input vcf we see variant 20:1230237 was not returned.
vcf_input <- readVcf(file, "hg19")
rowRanges(vcf_input)
rowRanges(vcf)

## This variant has no alternate allele and is called a
## monomorphic reference. The Ensembl VEP automatically
## drops these variants.
rowRanges(vcf)[,c("REF", "ALT")]

## -----
## Results written to disk
## -----
## Write a file to disk by providing a path and file name as 'output_file'.
## Different output file formats are specified using the 'dataformat'
```

```

## runtime options.

## Write a vcf file to myfile.vcf:
myparam <- VEPFlags(flags=list(vcf=TRUE,
  output_file="/path/myfile.vcf"))
## Write a gvf file to myfile.gvf:
myparam <- VEPFlags(flags=list(gvf=TRUE,
  output_file="/path/myfile.gvf"))

## -----
## Runtime options
## -----
## All runtime options are controlled by specifying a VEPFlags.
## See ?VEPFlags for complete details.
param <- VEPFlags()

## Logical options are turned on/off with TRUE/FALSE. By
## default, 'quiet' is FALSE.
## Setting 'quiet' to TRUE will suppress all status and warnings.
flags(param)$quiet <- TRUE

## Character options are turned on/off by specifying a character
## value or an empty character (i.e., character()). By default no
## 'sift' results are returned.
## Setting 'sift' to 'b' will return both predictions and scores.
flags(param)$sift <- 'b'

```

---

oldRuntimeOptions      *VEPParam runtime options*

---

## Description

Runtime options for the most current API version of the Ensembl Variant Effect Predictor.

## Details

VEPParam objects store the runtime options for querying the Ensembl Variant Effect Predictor (VEP). This page describes only the most current runtime options and is a condensed version of what is listed on the Ensembl web site:

[http://uswest.ensembl.org/info/docs/tools/vep/script/vep\\_options.html](http://uswest.ensembl.org/info/docs/tools/vep/script/vep_options.html)

Runtime options for archived versions can be found on the corresponding archive page.

<http://useast.ensembl.org/info/website/archives/index.html>

## Runtime options:

Data in the VEPParam are organized into the following categories, 'basic', 'input', 'cache', 'output', 'identifier', 'colocatedVariants', 'dataformat', 'filterqc', 'database' and 'advanced'. Each category

is a list of runtime options. logical options are turned on/off with TRUE/FALSE. character and numeric are 'on' when a character string is provided and 'off' when they contain an empty value (i.e., character() or numeric()).

'identifier', 'colocatedVariants', 'dataformat' are supported for VEPParam73 and later.

basic list of the following options:

- verbose: logical, default FALSE; output status messages
- quiet: logical, default FALSE; suppress status/warnings
- no\_progress: logical, default FALSE; don't show progress bars
- config: character, default character(); name of config file
- everything: logical, default FALSE; shortcut to switch on 12 options (sift, polyphen, ccds, hgvs, hgnc, numbers, domains, regulatory, cell\_type, canonical, protein and gmaf).
- fork: numeric, default numeric(); enable forking

input list of the the following options:

- species: character, default 'homo\_sapiens'; species for the data
- assembly: character, default character(); select assembly version if more than one available
- format: character, default character(); one of the following input file formats, 'ensembl', 'vcf', 'pileup', 'hgvs', 'id' or 'vep'. By default the script auto-detects the input file format.
- output\_file: character, default writes to temp file; path and file name of output file
- force\_overwrite: logical, default FALSE; overwrite the output file if it currently exists
- stats\_file: character, default character(); summary stats file name
- no\_stats: logical, default FALSE; do not generate a stats file
- stats\_text: logical, default FALSE; generate a plain text stats file instead of html
- html: logical, default FALSE; generate html version of the output file

cache list of the following options:

- cache: logical, default FALSE; enable use of cache
- dir: character, default '\$HOME/.vep/'; cache/plugin to be used
- dir\_cache: character, default '\$HOME/.vep/'; cache to be used
- dir\_plugins: character, default '\$HOME/.vep/'; plugin to be used
- offline: logical, default FALSE; enable offline mode, no database connections will be made
- fasta: character, default character(); FASTA filename or directory to files to use for reference sequences
- cache\_version: character, default character(); use a different cache version than the assumed default
- show\_cache\_info: logical, default FALSE; show source version information for selected cache and quit

output list of the following options:

- variant\_class: logical, default FALSE; output the sequence ontology variant class
- sift: character, default character(); output prediction, score or both, valid strings are 'p', 's' or 'b'

- polyphen: character, default character(); output prediction, score or both, valid strings are 'p', 's' or 'b'
- humdiv: logical, default FALSE; retrieve the humDiv PolyPhen prediction instead of humVar
- gene\_phenotype: logical, default FALSE; indicates if overlapped gene is associated with a phenotype, disease or trait
- regulatory: logical, default FALSE; identify overlaps with regulatory regions
- cell\_type: character, default character(); only report regulatory regions found in the given cell type(s)
- custom: character, default character(); name of custom annotation file to add to output. Currently only a single annotation is supported.
- plugin: character, default character(); name of plugin module. Currently only a single module is supported.
- individual: character, default character(); consider only alternate alleles present in the genotypes of 'all' or a character vector of specified individuals
- phased: logical, default FALSE; force VCF genotypes to be interpreted as phased
- allele\_number: logical, default FALSE; identify allele number from VCF input (1=first ALT, 2=second ALT, etc.)
- total\_length: character, default character(); cDNA, CDS and protein positions as position/length
- numbers: logical, default FALSE; output affected exon and intron numbering, format is Number/Total
- domains: logical, default FALSE; output names of overlapping protein domains
- no\_escape: logical, default FALSE; don't URI escape HGVS string
- keep\_csq: logical, default FALSE; don't overwrite existing CSQ entry in VCF INFO field
- vcf\_info\_field: character, default CSQ; change the name of the INFO key that VEP writes the consequences to in the VCF output.
- terms: character, default 'so'; type of consequence terms to output, valid strings are 'ensembl' or 'so'

identifiers list of the following options:

- hgvs: logical, default FALSE; add hgvs ID's
- shift\_hgvs: [0/1], default 1 (shift); enable or disable 3' shifting of HGVS notations
- protein: logical, default FALSE; add Ensembl protein ID's
- symbol: logical, default FALSE; add gene symbol (e.g. HGNC) (where available) to the output
- ccds: logical, default FALSE; add CCDS transcript ID's
- uniprot: logical, default FALSE; adds identifiers for translated protein products from three UniProt-related databases
- tsl: logical, default FALSE; adds the transcript support level for this transcript
- canonical: logical, default FALSE; indicate if transcript is cononical transcript for the gene
- biotype: logical, default FALSE; add biotype of transcript
- xref\_seq: logical, default FALSE; output aligned refseq mRNA ID

colocatedVariants list of the following options:

- check\_existing: logical, default FALSE; check for co-located variants
- check\_alleles: logical, default FALSE; when checking for co-located variants only report them if none of the alleles supplied are novel
- check\_svsv: logical, default FALSE; check for structural variants that overlap the input variants
- gmaf: logical, default FALSE; add global minor allele frequency (MAF) from 1000 Genomes Phase 1 data
- maf\_1kg: logical, default FALSE; add MAF from continental populations of 1000 Genomes Phase 1 data; must be use with `-cache`
- maf\_esp: logical, default FALSE; add MAF from NHLBI-ESP populations; must be used with `-cache`
- old\_maf: logical, default FALSE; for maf\_1kg and maf\_esp report only the frequency (no allele) and convert so it is always a minor frequency, i.e.  $< 0.5$
- pubmed: logical, default FALSE; report Pubmed IDs for publications that cite existing variant; must be used with `-cache`
- failed: logical, default FALSE; when checking for co-located variants include or exclude variants that have been flagged as failed

dataformat list of the following options:

- vcf: logical, default FALSE; write output in vcf format
- json: logical, default FALSE; write output in json format
- gvf: logical, default FALSE; write output in gcf format
- fields: character, default fields are 'Uploaded\_variation', 'Location', 'Allele', 'Gene', 'Feature', 'Feature\_type', 'Consequence', 'cDNA\_position', 'CDS\_position', 'Protein\_position', 'Amino\_acids', 'Codons' and 'Extra'. See [http://www.ensembl.org/info/docs/variation/vep/vep\\_formats.html#sv](http://www.ensembl.org/info/docs/variation/vep/vep_formats.html#sv) for details.
- convert: character, default character(); converts input file to one of 'ensembl', 'vcf', or 'pileup'
- minimal: logical, default FALSE; convert alleles to their most minimal representation before consequence calculation

filterqc list of the following options:

- check\_ref: logical, default FALSE; force check of supplied reference allele against the sequence stored in Ensembl Core database
- coding\_only: logical, default FALSE; return consequences in coding regions only
- chr: character, default character(); select a subset of chromosomes to be analyzed
- no\_intergenic: logical, default FALSE; do not include intergenic consequences
- pick: logical, default FALSE; pick once line of consequence data per variant
- pick\_allele: logical, default FALSE; pick once line of consequence data per variant allele
- flag\_pick: logical, default FALSE; as per `-pick`, but adds the PICK flag to the chosen block of consequence data and retains others.
- flag\_pick\_allele: logical, default FALSE; as per `-pick_allele`, but adds the PICK flag to the chosen block of consequence data and retains others.
- per\_gene: logical, default FALSE; output only the most severe consequence per gene

- `pick_order`: character, See ensembl web page for default order; customise the order of criteria applied when choosing a block of annotation data with e.g. `-pick`.
- `most_severe`: logical, default FALSE; output only most severe consequence per variation
- `summary`: logical, default FALSE; output a comma-separated list of all observed consequences per variation, transcript-specific columns will be left blank
- `filter_common`: logical, default FALSE; shortcut flag to turn on filters, See web page for details.
- `check_frequency`: logical, default FALSE; turn on frequency filtering, must also specify all of the `-freq_*` flags. See web page for details.
- `freq_pop`: character, default `character()`; population to use in frequency filter
- `freq_freq`: numeric, default `numeric()`; MAF to use in frequency filter
- `freq_gt_lt`: character, default `character()`; specify whether the frequency of the co-located variant must be greater than or less than the value specified. Values are 'gt' or 'lt'. in the `freq_freq` option.
- `freq_filter`: character, default `character()`; specify whether to exclude or include variants that pass the frequency filter. Values are 'exclude' or 'include'.
- `allow_non_variant`: logical, default FALSE; when using VCF format as input and output, by default VEP will skip all non-variant lines of input (i.e., where the ALT is NULL). When this option is enabled, lines will be printed in the VCF output with no consequence data added.

database list of the following options:

- `database`: logical, default TRUE; enable the VEP to use local or remote databases
- `host`: character, default `character()`; database host. This will use the default as defined by `vep 'ensdb.ensembl.org'`. Users in the US may find connection and transfer speeds quicker using the East coast mirror, `'useastdb.ensembl.org'`.
- `user`: character default `character()`; database user
- `password`: character, default `character()`; database password
- `port`: numeric, default `character()`; database port
- `genomes`: logical, default FALSE; override default connection settings with those for the Ensembl Genomes public MySQL server
- `gencode_basic`: logical, default FALSE; limit analysis to transcripts in GENCODE basic set
- `refseq`: logical, default FALSE; use otherfeatures database to retrieve transcripts
- `merged`: logical, default FALSE; use the merged Ensembl and RefSeq cache
- `all_refseq`: logical, default FALSE; include e.g. CCDS and Ensembl EST transcripts
- `lrg`: logical, default FALSE; map input variants to LRG coordinates
- `db_version`: numeric, default `character()`; force connection to specific version
- `registry`: character, default `character()`; provide file to override default connection settings

advanced list of the following options:

- `no_whole_genome`: logical, default FALSE; run in non-whole genome mode, variants analyzed one at a time, no caching



- `buffer_size`: numeric, default 5000; internal buffer size corresponding to number of variations read into memory simultaneously
- `write_cache`: logical, default FALSE; enable writing to the cache
- `build`: character, default `character()`; build cache for the selected species from the database (See `-chr` flag)
- `compress`: character, default `character()`; specify utility to decompress cached files (zcat is default)
- `skip_db_check`: logical, default FALSE; force the script to use a cache built from a different host than specified with `-host`
- `cache_region_size`: numeric, default `numeric()`; size in base-pairs of the region covered by one file in the cache, see full description of this flag on the web site for details

### Author(s)

Valerie Obenchain

### See Also

- The `ensemblVEP` function man page.
- The `VEPParam` class man page.

### Examples

```
## See ?VEPParam for examples of constructing instances of a
## VEPParam object with different runtime options.
```

---

<code>parseCSQToGRanges</code>	<i>Parse the CSQ column of a VCF object into a GRanges object</i>
--------------------------------	---

---

### Description

Parse the CSQ column in a VCF object returned from the Ensembl Variant Effect Predictor (VEP).

### Usage

```
## S4 method for signature 'character'
parseCSQToGRanges(x, VCFRowID=character(),
  ..., info.key = "CSQ")
## S4 method for signature 'VCF'
parseCSQToGRanges(x, VCFRowID=character(),
  ..., info.key = "CSQ")
```

**Arguments**

x	The character name of a vcf file on disk or a VCF object
VCFRowID	A character vector of rownames from the original VCF. When provided, the result includes a metadata column named 'VCFRowID' which maps the result back to the row (variant) in the original VCF. When VCFRowID is not provided no 'VCFRowID' column is included.
info.key	The name of the INFO key that VEP writes the consequences to in the output (default is CSQ). This should only be used if something other than CSQ was passed in the <code>-vcf_info_field</code> flag in the output options.
...	Arguments passed to other methods. Currently not used.

**Details**

- When `ensemblVEP` returns a VCF object, the consequence data are returned unparsed in the 'CSQ' INFO column. `parseCSQToGRanges` parses these data into a `GRanges` object that is expanded to match the dimension of the 'CSQ' data. Because each variant can have multiple matches, the ranges in the `GRanges` are repeated.

If rownames from the original VCF are provided as `VCFRowID` a metadata column is included in the result that maps back to the row (variant) in the original VCF. This option is only applicable when the `info.key` field has data (is not empty).

If no `info.key` column is found the function returns the data in `rowRanges()`.

**Value**

Returns a `GRanges` object with consequence data as the metadata columns. If no 'CSQ' column is found the `GRanges` from `rowRanges()` is returned.

**Author(s)**

Valerie Obenchain

**References**

Ensembl VEP Home: <http://uswest.ensembl.org/info/docs/tools/vep/index.html>

**See Also**

[ensemblVEP VEPPParam-class](#)

**Examples**

```
file <- system.file("extdata", "ex2.vcf", package="VariantAnnotation")
vep <- ensemblVEP(file, param=VEPFlags(flags=list(vcf=TRUE, host="useastdb.ensembl.org")))

## The returned 'CSQ' data are unparsed.
info(vep)$CSQ

## Parse into a GRanges and include the 'VCFRowID' column.
```

```
vcf <- readVcf(file, "hg19")
csq <- parseCSQToGRanges(vep, VCFRowID=rownames(vcf))
csq[1:4]
```

---

runtimeOptions

*VEPParam runtime options*

---

## Description

Runtime options for the most current API version of the Ensembl Variant Effect Predictor.

## Details

VEPFlags objects store the runtime options for querying the Ensembl Variant Effect Predictor (VEP). This page describes only the most current runtime options and is a condensed version of what is listed on the Ensembl web site:

[http://uswest.ensembl.org/info/docs/tools/vep/script/vep\\_options.html](http://uswest.ensembl.org/info/docs/tools/vep/script/vep_options.html)

Runtime options for archived versions can be found on the corresponding archive page.

<http://useast.ensembl.org/info/website/archives/index.html>

## Author(s)

Lori Shepherd

## See Also

- The `ensemblVEP` function man page.
- The `VEPFlags` class man page.

## Examples

```
## See ?VEPFlags for examples of constructing instances of a
## VEPFlags object with different runtime options.
```

---

 VEPFlags-class

*VEPFlag objects*


---

## Description

VEPFlags stores runtime options for the Ensembl Variant Effect Predictor.

## Details

- The VEPFlags family of objects stores runtime options for querying the Ensembl Variant Effect Predictor (VEP). For complete details, see the Ensembl VEP web page.  
[http://uswest.ensembl.org/info/docs/tools/vep/script/vep\\_options.html](http://uswest.ensembl.org/info/docs/tools/vep/script/vep_options.html)

## Runtime options

For a description of runtime options for the most current version of the API see the ?runtimeOptions man page or the Ensembl web site:

[http://www.ensembl.org/info/docs/tools/vep/script/vep\\_options.html](http://www.ensembl.org/info/docs/tools/vep/script/vep_options.html)

Runtime options for archived versions can be found on the corresponding archive page.

## Constructor

- VEPFlags(version=max(unlist(currentVEP())),scriptPath=character(), flags=list(), ...) Creates a VEPFlags object.  
 version Numeric specifying the Ensembl API version(s) supported.  
 flags list of runtime options  
 scriptPath character path to variant\_effect\_predictor.pl script; applicable when multiple versions of the script are installed locally

## Accessors

In the following code, x is a VEPFlags object and value is a named list or character vector.

- flags(x), flags(x) <- value

## Helper functions

- currentVEP(): Invoked with no arguments. Returns the most current VEPFlags class and supported Ensembl API versions.
- supportedVEP(): Invoked with no arguments. Returns a list of VEPParam and VEPFlags subclasses and the Ensembl API versions they support.

The following functions create a list of runtime options and are used in the VEPFlags constructor.

- flagOpts(version, ...)

**Author(s)**

Lori Shepherd

**See Also**

- The runtimeOptions man page.
- The ensemblVEP function man page.
- The VEPPParam class page for archived API versions.

**Examples**

```
## -----
## Current API version
## -----
## The default constructor supports the most current version
## of the Ensembl variant API.
param <- VEPFlags()
class(param)

## The 'version' slot lists all API versions supported by the class.
version(param)

## The 'supportedVEP' helper returns a list of VEPPParam and VEPFlags
## classes and the corresponding API versions it support.
supportedVEP()

## -----
## Archived API versions
## -----
## Create a VEPPParam for an archived version by supplying the
## version to the constructor.
## See ?VEPPParam for more details

## Note on host: A host is not assigned by default and therefore will
## use the VEP host default of "ensemldb.ensembl.org". Users in the
## US may find connection and transfer speeds quicker using our East
## coast mirror, "useastdb.ensembl.org"
param <- VEPFlags(flags=list(host="useastdb.ensembl.org"))

## By default the VEP script used is the one found in the PATH.
## To specify a script in a non-standard location use the 'scriptPath'
## setter. Include the full path and the name of the script with the
## .pl extension.
## Not run:
scriptPath(param) <- "fullPathToScript/vep.pl"

## End(Not run)

## -----
## Manipulation
## -----
```

```

## View the runtime values in 'flags'.
flags(param)

## Change the value of the 'everything' to TRUE.
flags(param)$everything
flags(param)$everything <- TRUE
flags(param)$everything

## Replace multiple values using a named list.
flags(param) <- list(verbose=TRUE, config="myconfig.txt")
flags(param)

## Write the output to myfile.vcf instead of returning a VCF object.
## Return the sift and polyphen predictions only (not scores).
param <- VEPFlags(flags=list(output_file="path/myfile.vcf",
  sift="p", polyphen="p"))

## 'sift' and 'polyphen' are runtime options that require
## a character value, (i.e., 's', 'p', or 'b').
flags(param)$sift

```

---

VEPPParam-class

*VEPPParam objects*


---

## Description

VEPPParam is a VIRTUAL class with concrete subclasses that store runtime options for the Ensembl Variant Effect Predictor.

## Details

- The VEPPParam family of objects stores runtime options for querying the Ensembl Variant Effect Predictor (VEP). Brief descriptions of the options are provided below. For complete details, see the Ensembl VEP web page.

[http://uswest.ensembl.org/info/docs/tools/vep/script/vep\\_options.html](http://uswest.ensembl.org/info/docs/tools/vep/script/vep_options.html)

- VEPPParam subclasses: As of ensemblVEP version  $\geq 1.3.3$  a new subclass of VEPPParam is created when there is a substantial change in the Ensembl variant database API. The subclass will support all versions up until the next 'substantial' version change. The version accessor on a VEPPParam object lists all versions that particular VEPPParam class supports. By default the VEPPParam constructor creates a subclass that supports the current version. To create a VEPPParam for a specific version, supply the version as an argument. Use supportedVEP() to see all supported versions.

- Archived versions: Past versions of the VEP script and corresponding data are available on the Ensembl archive page.

<http://uswest.ensembl.org/info/website/archives/index.html>

Archived scripts can query cached data or perform a live query against the European mirror. (The US mirror, useastdb, hosts the current release only.) The appropriate version of cached data can be downloaded from the same page as the archived script.

- Multiple versions: By default, the `variant_effect_predictor.pl` script found in the `PATH` is the script used. If multiple versions of the script are installed locally a few steps must be taken to ensure the proper version is used.
  - `scriptPath` Provide the full path to the `variant_effect_predictor.pl` script (including the `.pl` extension) as the `scriptPath` argument to the `VEPParam` constructor.
  - `cache directories` By default, the cache runtime options `dir`, `dir_cache` and `dir_plugins` are set to `$HOME/.vep`. These locations need to be specified if the data are not in the default `$HOME/.vep` location.

### Runtime options

For a description of runtime options for the most current version of the API see the `?runtimeOptions` man page or the Ensembl web site:

[http://www.ensembl.org/info/docs/tools/vep/script/vep\\_options.html](http://www.ensembl.org/info/docs/tools/vep/script/vep_options.html)

Runtime options for archived versions can be found on the corresponding archive page.

### Constructor

- `VEPParam(version=max(unlist(currentVEP()), basic=basicOpts(), input=inputOpts(), cache=cacheOpts(), output=outputOpts(), filterqc=filterqcOpts(), database=databaseOpts(), advanced=advancedOpts(), identifier=identifierOpts(), colocatedVariants=colocatedVariantsOpts(), dataformat=dataformatOpts(), scriptPath=character(), ...)` Creates a `VEPParam` object.

`version` Numeric specifying the Ensembl API version(s) supported.

`basic` list of basic options

`input` list of input options

`cache` list of cache options

`output` list of output options

`filterqc` list of filterqc options

`database` list of database options

`advanced` list of advanced options

`scriptPath` character path to `variant_effect_predictor.pl` script; applicable when multiple versions of the script are installed locally

Supported for `VEPParam73` and later:

`identifier` list of identifier options

`colocatedVariants` list of `colocatedVariants` options

`dataformat` list of `dataformat` options

### Accessors

In the following code, `x` is a `VEPParam` object and `value` is a named list or character vector.

- `basic(x), basic(x) <- value`
- `input(x), input(x) <- value`
- `cache(x), cache(x) <- value`

- `output(x)`, `output(x) <- value`
- `filterqc(x)`, `filterqc(x) <- value`
- `database(x)`, `database(x) <- value`
- `advanced(x)`, `advanced(x) <- value`
- `version(x)`, `version(x) <- value`
- `scriptPath(x)`, `scriptPath(x) <- value`

Supported for VEPPParam73 and later:

- `identifier(x)`, `identifier(x) <- value`
- `colocatedVariants(x)`, `colocatedVariants(x) <- value`
- `dataformat(x)`, `dataformat(x) <- value`

### Helper functions

- `currentVEP()`: Invoked with no arguments. Returns the most current VEPPParam class and supported Ensembl API versions. A single class may support more than one version.
- `supportedVEP()`: Invoked with no arguments. Returns a list of VEPPParam subclasses and the Ensembl API versions they support.

The following functions create a list of runtime options and are used in the VEPPParam constructor.

- `basicOpts(version, ...)`
- `inputOpts(version, ...)`
- `cacheOpts(version, ...)`
- `outputOpts(version, ...)`
- `filterqcOpts(version, ...)`
- `databaseOpts(version, ...)`
- `advancedOpts(version, ...)`

Supported for VEPPParam73 and later:

- `identifierOpts(version, ...)`
- `colocatedVariantsOpts(version, ...)`
- `dataformatOpts(version, ...)`

### Author(s)

Valerie Obenchain and Lori Shepherd

### See Also

- The `runtimeOptions` man page.
- The `ensemblVEP` function man page.
- The `VEPFlags` class page for current API.



**Examples**

```

## -----
## Archived API versions
## -----
## Create a VEPPParam for an archived version by supplying the
## version to the constructor.
## See ?VEPFlags for Current API version
param <- VEPPParam(version=85)
class(param)

## The 'version' slot lists all API versions supported by the class.
version(param)

## The 'supportedVEP' helper returns a list of VEPPParam classes and the
## corresponding API versions they support.
supportedVEP()

## A different archived version
param67 <- VEPPParam(67)
param67

## Archive versions can query the cache or the European mirror. The
## default 'host' for live queries is set to 'ensemldb.ensembl.org'.
database(param67)$host

## By default the VEP script used is the one found in the PATH.
## To specify a script in a non-standard location use the 'scriptPath'
## setter. Include the full path and the name of the script with the
## .pl extension.
## Not run:
scriptPath(param) <- "fullPathToScript/variant_effect_predictor.pl"

## End(Not run)

## -----
## Manipulation
## -----

## View the values in 'basic' and 'input'.
basic(param)
input(param)

## Change the value of the 'everything' to TRUE.
basic(param)$everything
basic(param)$everything <- TRUE
basic(param)$everything

## Replace multiple values using a named list.
basic(param) <- list(verbose=TRUE, config="myconfig.txt")
basic(param)

## Write the output to myfile.vcf instead of returning a VCF object.

```

```
## Return the sift and polyphen predictions only (not scores).
param <- VEPPParam(input=c(output_file="path/myfile.vcf"),
  output=c(sift="p", polyphen="p"), version=88)

## 'sift' and 'polyphen' are runtime options that require
## a character value, (i.e., 's', 'p', or 'b').
output(param)$sift

## To turn off 'sift' or 'polyphen' set the value to an
## empty character (i.e., character()).
output(param)$sift <- character()
```

# Index

- \* **classes**
  - VEPFlags-class, [12](#)
  - VEPParam-class, [14](#)
- \* **methods**
  - ensemblVEP, [2](#)
  - parseCSQToGRanges, [9](#)
  - VEPFlags-class, [12](#)
  - VEPParam-class, [14](#)
- \* **utilities**
  - oldRuntimeOptions, [4](#)
  - runtimeOptions, [11](#)
  
- advanced (VEPParam-class), [14](#)
- advanced, VEPParam-method (VEPParam-class), [14](#)
- advanced<- (VEPParam-class), [14](#)
- advanced<-, VEPParam-method (VEPParam-class), [14](#)
- advancedOpts (VEPParam-class), [14](#)
  
- basic (VEPParam-class), [14](#)
- basic, VEPParam-method (VEPParam-class), [14](#)
- basic<- (VEPParam-class), [14](#)
- basic<-, VEPParam-method (VEPParam-class), [14](#)
- basicOpts (VEPParam-class), [14](#)
  
- cache (VEPParam-class), [14](#)
- cache, VEPParam-method (VEPParam-class), [14](#)
- cache<- (VEPParam-class), [14](#)
- cache<-, VEPParam-method (VEPParam-class), [14](#)
- cacheOpts (VEPParam-class), [14](#)
- class:VEPFlags (VEPFlags-class), [12](#)
- class:VEPParam (VEPParam-class), [14](#)
- class:VEPParam67 (VEPParam-class), [14](#)
- class:VEPParam73 (VEPParam-class), [14](#)
- class:VEPParam75 (VEPParam-class), [14](#)
- class:VEPParam77 (VEPParam-class), [14](#)
- class:VEPParam78 (VEPParam-class), [14](#)
- class:VEPParam82 (VEPParam-class), [14](#)
- class:VEPParam88 (VEPParam-class), [14](#)
- colocatedVariants (VEPParam-class), [14](#)
- colocatedVariants, VEPParam73-method (VEPParam-class), [14](#)
- colocatedVariants, VEPParam75-method (VEPParam-class), [14](#)
- colocatedVariants, VEPParam77-method (VEPParam-class), [14](#)
- colocatedVariants, VEPParam78-method (VEPParam-class), [14](#)
- colocatedVariants, VEPParam82-method (VEPParam-class), [14](#)
- colocatedVariants, VEPParam88-method (VEPParam-class), [14](#)
- colocatedVariants<- (VEPParam-class), [14](#)
- colocatedVariants<-, VEPParam73-method (VEPParam-class), [14](#)
- colocatedVariants<-, VEPParam75-method (VEPParam-class), [14](#)
- colocatedVariants<-, VEPParam77-method (VEPParam-class), [14](#)
- colocatedVariants<-, VEPParam78-method (VEPParam-class), [14](#)
- colocatedVariants<-, VEPParam82-method (VEPParam-class), [14](#)
- colocatedVariants<-, VEPParam88-method (VEPParam-class), [14](#)
- colocatedVariantsOpts (VEPParam-class), [14](#)
- currentVEP (VEPFlags-class), [12](#)
  
- database (VEPParam-class), [14](#)
- database, VEPParam-method (VEPParam-class), [14](#)
- database<- (VEPParam-class), [14](#)
- database<-, VEPParam-method (VEPParam-class), [14](#)

- databaseOpts (VEPParam-class), 14
- dataformat (VEPParam-class), 14
- dataformat, VEPParam73-method (VEPParam-class), 14
- dataformat, VEPParam75-method (VEPParam-class), 14
- dataformat, VEPParam77-method (VEPParam-class), 14
- dataformat, VEPParam78-method (VEPParam-class), 14
- dataformat, VEPParam82-method (VEPParam-class), 14
- dataformat, VEPParam88-method (VEPParam-class), 14
- dataformat<- (VEPParam-class), 14
- dataformat<-, VEPParam73-method (VEPParam-class), 14
- dataformat<-, VEPParam75-method (VEPParam-class), 14
- dataformat<-, VEPParam77-method (VEPParam-class), 14
- dataformat<-, VEPParam78-method (VEPParam-class), 14
- dataformat<-, VEPParam82-method (VEPParam-class), 14
- dataformat<-, VEPParam88-method (VEPParam-class), 14
- dataformatOpts (VEPParam-class), 14
- ensemblVEP, 2, 10
- ensemblVEP, character-method (ensemblVEP), 2
- filterqc (VEPParam-class), 14
- filterqc, VEPParam-method (VEPParam-class), 14
- filterqc<- (VEPParam-class), 14
- filterqc<-, VEPParam-method (VEPParam-class), 14
- filterqcOpts (VEPParam-class), 14
- flagOpts (VEPFlags-class), 12
- flags (VEPFlags-class), 12
- flags, VEPFlags-method (VEPFlags-class), 12
- flags<- (VEPFlags-class), 12
- flags<-, VEPFlags-method (VEPFlags-class), 12
- identifier (VEPParam-class), 14
- identifier, VEPParam73-method (VEPParam-class), 14
- identifier, VEPParam75-method (VEPParam-class), 14
- identifier, VEPParam77-method (VEPParam-class), 14
- identifier, VEPParam78-method (VEPParam-class), 14
- identifier, VEPParam82-method (VEPParam-class), 14
- identifier, VEPParam88-method (VEPParam-class), 14
- identifier<- (VEPParam-class), 14
- identifier<-, VEPParam73-method (VEPParam-class), 14
- identifier<-, VEPParam75-method (VEPParam-class), 14
- identifier<-, VEPParam77-method (VEPParam-class), 14
- identifier<-, VEPParam78-method (VEPParam-class), 14
- identifier<-, VEPParam82-method (VEPParam-class), 14
- identifier<-, VEPParam88-method (VEPParam-class), 14
- identifierOpts (VEPParam-class), 14
- input (VEPParam-class), 14
- input, VEPParam-method (VEPParam-class), 14
- input<- (VEPParam-class), 14
- input<-, VEPParam-method (VEPParam-class), 14
- inputOpts (VEPParam-class), 14
- oldRuntimeOptions, 4
- output (VEPParam-class), 14
- output, VEPParam-method (VEPParam-class), 14
- output<- (VEPParam-class), 14
- output<-, VEPParam-method (VEPParam-class), 14
- outputOpts (VEPParam-class), 14
- parseCSQToGRanges, 9
- parseCSQToGRanges, character-method (parseCSQToGRanges), 9
- parseCSQToGRanges, VCF-method (parseCSQToGRanges), 9

runtimeOptions, 11

scriptPath (VEPPParam-class), 14

scriptPath<- (VEPPParam-class), 14

show, VEPFlags-method (VEPFlags-class),  
12

show, VEPPParam-method (VEPPParam-class),  
14

supportedVEP (VEPFlags-class), 12

VCF, 2

VEPFlags (VEPFlags-class), 12

VEPFlags-class, 3, 12

VEPPParam (VEPPParam-class), 14

VEPPParam-class, 10, 14

VEPPParam67-class (VEPPParam-class), 14

VEPPParam73-class (VEPPParam-class), 14

VEPPParam75-class (VEPPParam-class), 14

VEPPParam77-class (VEPPParam-class), 14

VEPPParam78-class (VEPPParam-class), 14

VEPPParam82-class (VEPPParam-class), 14

VEPPParam88-class (VEPPParam-class), 14

version (VEPPParam-class), 14

version<- (VEPPParam-class), 14